

440/455 NGL TRAVELING AXLE TRAILER



- Easy to Operate Control Panel
- Enhanced Lighted Control Panel
- Optional Wireless Remote Control



- Easy Hook Up Hydraulics
- Upper Deck Lighted Toolboxes



- 8 LED Tail Light System



- Smooth Transition to Upper Deck



- Centralized Grease System Located at Bumper
- 6 Zerks (440)
- 8 Zerks (455)



- 6.5° Low Load Angle



PROVEN SOLUTIONS FOR YOUR HAULING NEEDS!
1-800-428-5655 | www.landoll.com/trailers

STANDARD & OPTIONAL EQUIPMENT / FEATURES

Model 440/455 Traveling Axle Trailer

S=Standard O=Optional

MODEL 455	55 TON	110,000 lbs
MODEL 440	40 TON	80,000 lbs
MAIN FRAME		
- Fabricated 80,000 and 100,000 PSI Yield Beams	S	S
- Four Beam Design	S	S
KINGPIN SETTING		
- 21" Setting	S	S
- 83 1/2" Swing Clearance	S	S
- 2" 5th-Wheel Kingpin Hitch	S	S
CROSSMEMBERS		
- Alternating 4" and 3" Jr. I-Beam on 8" Centers	S	
- 4" Jr. I-Beam on 8" Centers		S
WINCH		
- 12,000 lb Worm Gear with Spring Tension and 85' of 1/2" Cable	S	S
- 20,000 lb Worm Gear with Spring Tension and 85' of 5/8" Cable	O	O
- 20,000 lb Planetary 2-Speed and 85' of 5/8" Cable	O	O
- 30,000 lb Planetary 2-Speed and 85' of 5/8" Flex 9 Cable	O	O
DECK AND FEATURES		
- 102" Wide		S
- Deck Rating 50,000 lb in 10'	S	
- Deck Rating 70,000 lb in 10'		S
- 90° Slope Drop	S	S
- 37" Deck Height (Loaded with 17.5 Tires and 48" King Pin Height) – Add 5" for 22.5 Tires	S	S
- 1 3/8" Apitong Hardwood Deck	S	S
- Aluminum Pullouts to 13' Wide	O	O
- 6.5° Load Angle	S	S
- Landoll Hoses and Components Certified to -40°F	S	S
ACCESSORIES		
- Flat Approach Plate with 6 Keyhole Tie Downs	S	S
- Automatic Slack Adjusters	S	S
- Main Deck Center Slope Roller	S	S
- Upper Deck Slope Rollers	O	O
TIE DOWNS / CHAIN GOTCHAS		
- Double Keyhole Chain Slots with Square Stake Pockets on 16" Centers	S	S
TOOL BOX (UPPER DECK, BOTH SIDES)		
- Non-Weight Bearing Top Opening, Lighted Tool Box	S	S
- Weight Bearing Top Opening, Lighted Tool Box	O	O
- Side Opening Door, Lighted Tool Box	O	O
PARKING STANDS		
- Jost Two Speed Landing Gear	S	S
- Pin Drop	S	S

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.



MODEL 455	55 TON	110,000 lbs
MODEL 440	40 TON	80,000 lbs
SUSPENSION / AXLES		
- SAF-Holland/Neway Air Ride RLU228, 22,500 lb Capacity	S	S
- Dock Level Hydraulic 62,000 lb Capacity (Not Available with 215/75R 17.5 Low-Pro Tires)	O	O
- Centralized Grease System	S	S
- (2) 25,000 lb Axles, Dual Tire, Oil Bath Bearings	S	
- (3) 25,000 lb Axles, Dual Tire, Oil Bath Bearings		S
BRAKES		
- 12.25x7.5 Full Air / Spring Brakes ABS, 4S2M	S	S
- 16.5x7 Full Air / Spring Brakes ABS, 4S2M	O	O
- Disc Brake Option	O	O
TIRES / RIMS		
- 235/75R 17.5 Double Coin Tires on 17.5x6.75 Tubeless Rims	S	S
- 255/70R 22.5 Double Coin Tires on 22.5x7.5 Tubeless Rims	O	O
- 255/70R 22.5 Michelin Tires on 22.5x7.5 Tubeless Rims	O	O
- All Axles Prepped for Tire Inflation	S	S
- Tire Inflation System	O	O
- Hubometer	O	O
HYDRAULIC HOOK UP		
- Quick Couplers 2,500 PSI - 20 GPM at Controls, 50 GPM Max	S	S
LIGHTS		
- Grote Rubber Grommet Mounted Annealed LED Lighting	S	S
- Grote "Xtreme" Wiring Harness	S	S
- Center Mounted Side Turn Signal	S	S
- Slope Mounted Rear Facing Work Lights	O	O
- Prepped for Slope Mounted Work Light Option	S	S
- Center Rear Strobe Light	S	S
- Mud Flap, Stop, Turn and Tail Lights	S	S
FINISH / COLOR		
- Steel Grit Shot Blast to Bright Metal	S	S
- Zinc Rich Primer	S	S
- TGIC Polyester Powder Coat White, Black, Yellow, Blue, Red, Green, Sapphire Blue, Dark Gray	S	S
- Galvanizing	O	O
WEIGHT (ESTIMATED)		
- 440-41' - 16,820 lbs +/-3%	S	
- 440-45' - 17,700 lbs +/-3%	S	
- 440-48' - 18,575 lbs +/-3%	S	
- 440-50' CA - 19,355 lbs +/-3%	S	
- 440-53' - 19,610 lbs +/-3%	S	
- 455-48' - 21,980 lbs +/-3%		S
- 455-50' - 23,010 lbs +/-3%		S
- 455-50' CA - 22,945 lbs +/-3%		S
- 455-53' - 24,485 lbs +/-3%		S
- 455-57' - 25,750 lbs +/-3%		S

**MORE OPTIONS AVAILABLE
INCLUDING WIRELESS REMOTE CONTROL
KICKER ROLLERS OR RAILROAD DECK
CONSULT FACTORY**

SCAN FOR MORE



CALL 1-800-428-5655

REMEMBER: QUALITY IS ALWAYS A BARGAIN!

1900 North Street | Marysville, KS 66508 | Phone:785-562-5381 | Fax:888-293-6779