

# 326/327/329 DETACHABLE GOOSENECK



*Pictured with Optional Beavertail Heavy Duty Ramps, Weld-On Wheel Covers with Traction Bars, Boom Trough Cover and Swing-Out Outriggers*



**PROVEN SOLUTIONS FOR YOUR HAULING NEEDS!**  
1-800-428-5655 | [www.landoll.com/trailers](http://www.landoll.com/trailers)

# STANDARD & OPTIONAL EQUIPMENT / FEATURES

## Model 326 / 327 / 329 Detachable Gooseneck

S=Standard O=Optional

MODEL 326	35 TON	70,000 lbs
MODEL 327	50 TON	100,000 lbs
MODEL 329	60 TON	120,000 lbs
<b>MAIN FRAME</b>		
- Fabricated 16", 100,000 PSI Flange	S	S
- Capacity - 70,000 lb in 16'	S	S
- Capacity - 100,000 lb in 16'	S	S
- Capacity - 120,000 lb in 10'	S	S
<b>KINGPIN SETTING</b>		
- 15" for 84" Swing Clearance (10' 7" Neck)	S	S
- 15" for 113" Swing Clearance / 42" for 86 Swing Clearance (13' Neck)	S	O
<b>CROSSMEMBERS</b>		
- 8" High Tensile I-Beams on 24" Centers	S	S
- 8" High Tensile I-Beams on 20" Centers	S	S
<b>GOOSENECK, DECK &amp; ACCESSORIES</b>		
- 10'7"	S	S
- 13" Gooseneck with 86" and 113" Swing Clearance	S	O
- 13' HD with Provision for Flip Ext.	S	S
- 102" Wide	S	S
- 8" Loaded Ground Clearance	S	S
- 24" Loaded Deck Height	S	S
- Fifth-Wheel Type Automatic Gooseneck Lock with Lock / Unlock Visual from Tractor	S	S
- Centralized Grease System	S	S
- Automatic Slack Adjusters	S	S
- Rail Stiffeners	S	S
- Ramp Brackets and Outtrigger Brackets	S	S
- Boom Trough	S	S
- Front Bolsters	S	S
- Swing-Out Riggers	O	O
- Landoll Hoses & Components Certified to -40°	S	S
<b>TIE DOWNS / CHAIN GOTCHAS</b>		
- 8 "D"-Rings	S	S
- 10 "D"-Rings	S	S
<b>STORAGE AREA</b>		
- 41"W x 24"L x 10"D Between Main Frames	S	S
- 41"W x 20"L x 10"D Between Main Frames	S	S

MODEL 326	35 TON	70,000 lbs
MODEL 327	50 TON	100,000 lbs
MODEL 329	60 TON	120,000 lbs
<b>SUSPENSION / AXLES</b>		
- SAF-Holland / Neway Air Ride (RLU250) 25,000 lb Capacity	S	S
- (2) 25,000 lb Dual Tire, Oil Bath Bearings	S	S
- (3) 25,000 lb Dual Tire, Oil Bath Bearings	S	S
<b>BRAKES</b>		
- 16.5x7 Full Air / Spring Brakes ABS, 4S2M / Center Axle Indirect	S	S
<b>TIRES / RIMS</b>		
- 255/70R 22.5 LRH Radial	S	S
- 295/75R 22.5 LRG Radial	S	S
- 22.5x8.25 10-Bolt Hub Pilot	S	S
<b>HYDRAULIC HOOK UP</b>		
- Hydraulic Quick Couplers / 2,500 PSI - 15 GPM	S	S
<b>LIGHTS</b>		
- Grote Rubber Grommet Mounted Annealed LED Lighting	S	S
- Grote "Xtreme" Wiring Harness (7-Year Warranty)	S	S
<b>FINISH / COLOR</b>		
- Steel Grit Shot Blast to Bright Metal	S	S
- Zinc Rich Primer	S	S
- TGIC Polyester Powder Coat White, Black, Yellow, Blue, Red, Green, Sapphire Blue, Dark Gray	S	S
<b>WEIGHT (ESTIMATED)</b>		
- 13,250 lbs (44') +/- 3%	S	S
- 18,900 lbs (48') +/- 3%	S	S
- 22,500 lbs (51') +/- 3%	S	S
<b>MORE OPTIONS AVAILABLE -- CONSULT FACTORY</b>		

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.



**CALL 1-800-428-5655**

**REMEMBER: QUALITY IS ALWAYS A BARGAIN!**

1900 North Street | Marysville, KS 66508 | Phone:785-562-5381 | Fax:888-293-6779

SCAN FOR MORE

