MODEL 345 PINTLE HITCH TRAILER



















PROVEN SOLUTIONS FOR YOUR HAULING NEEDS!

STANDARD & OPTIONAL EQUIPMENT/FEATURES

Model 345 Pintle Hitch Trailer

S=Standard O=Optional

s s s

s

s s s

S

s s

s s s

MODEL 345 25 TON 50,000 lbs	MODEL 345 25 TON 50,000 lbs
MAIN FRAME - Fabricated 80,000 PSI Yield Four Beam Design - Fabricated Inner Beams 80,000 PSI Web and Top Flange, 100,000 PSI Bottom Flange	
нітсн	PARKING STANDS - Pin Drop
 Pintle Hook with 15,000 lb Vertical Load Eye with Adjustment of 23"-32" 4' Hitch for Tractor without Bed Overhang 5' Hitch for Tractor with 1' Bed Overhang 7' Hitch for Tractor with 3' Bed Overhang 	SUSPENSION / AXLES - SAF-Holland / Neway Air Ride RLU228, 22,500 lb Capacity - Centralized Grease System - (2) 25,000 lb Dual Tires, Oil Bath Bearings
CROSSMEMBERS - 3" & 4" Jr. I-Beams Alternating on 8" Centers	BRAKES - 12.25x7.5 Full Air / Spring Brakes ABS, 4S2M
WINCH - None - 12,000 lb Braden - Front Mount - 20,000 lb Braden - Front Mount - Cable Roller Guide for Winch	- 17.5x6.75 Tubeless Rims
- Wireless Remote Control	HYDRAULIC HOOK UP - Hydraulic Quick Couplers 2500 PSI - 20 GPM at Controls, 50 GPM Max LIGHTS - Grote Rubber Grommet Mounted Annealed LED Lighting - Grote "Xtreme" Wiring Harness (7-Year Warranty)
DECK AND FEATURES - 102" Wide - 13/8" Apitong - Deck Rating 40,000 lb in 10'	
- 9° Load Angle - Landoll Hoses and Components Certified to -40°F	FINISH / COLOR - Steel Grit Shot Blast to Bright Metal - Zinc Rich Primer - TGIC Polyester Powder Coat White, Black, Yellow, Blue, Red, Green, Sapphire Blue, Dark Gray
ACCESSORIES - Approach Plate with (6) Keyhole Tie Downs - Dual Hydraulic Controls Street and Curb Side	
TIE DOWNS / CHAIN GOTCHAS - Double Keyhole Chain Slots and Stake Pockets on 24" Centers	WEIGHT - 13,500 lbs +/-3%





CALL 1-800-428-5655

REMEMBER: QUALITY IS ALWAYS A BARGAIN!

1900 North Street | Marysville, KS 66508 | Phone:785-562-5381 | Fax:888-293-6779

