



Agricultural Seeder Specifications

Three-Point Hitch Models (4ft. to 6 ft.)

Product Attributes	SSP-4	SSP-5	SSP-6
Approximate Weight	844 lbs. (380 kg)	1,007 lbs. (453 kg)	1,100 lbs. (495 kg)
Working Width	4 ft. 0 in. (1.2 m)	5 ft. 0 in. (1.25 m)	6 ft. 0 in. (1.8 m)
Transport Width	5 ft. 0 in. (1.25 m)	6 ft. 0 in. (1.8 m)	7 ft. 0 in. (2.1 m)
Transport Height	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor
Overall Height	3 ft. 7 in. (1.08 m)	3 ft. 7 in. (1.08 m)	3 ft. 7 in. (1.08 m)2
Overall Length	2 ft. 6 in. (0.8 m)	2 ft. 6 in. (0.8 m)	2 ft. 6 in. (0.8 m)
Seed Box	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover
Seed Box Capacity - Meter Box	1.75 bu.	2.187 bu.	2.625 bu.
Seed Box Capacity - Agitator Box	1.75 bu.	2.187 bu.	2.625 bu.
Seed Meters	"Micro-Meter" / Blade Agitator	"Micro-Meter" / Blade Agitator	"Micro-Meter" / Blade Agitator
Seed Meter Drive	Ground Driven	Ground Driven	Ground Driven
Seed Meter/Opening Space	8 in. (203 mm) / 4 in. (102 mm)	8 in. (203 mm) / 4 in. (102 mm)	8 in. (203 mm) / 4 in. (102 mm)
Seed Delivery	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray
Pulverizer Roller - Front	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron
Pulverizer Roller - Rear	9.5 in. (241 mm) Gray Cast Iron	9.5 in. (241 mm) Gray Cast Iron	9.5 in. (241 mm) Gray Cast Iron
Pulverizer Axle Bearings	Greaseable	Greaseable	Greaseable
Pulverizer Axle Size - Front	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)
Pulverizer Axle Size - Rear	1.75 in. (44.5 mm)	1.75 in. (44.5 mm)	1.75 in. (44.5 mm)
Three-Point Hitch	Cat. I, II Free Link; Cat. I Quick Coupler Hitch	Cat. I, II Free Link; Cat. I Quick Coupler Hitch	Cat. I, II Free Link; Cat. I Quick Coupler Hitch
Cat. II Quick Coupler Hitch Adaptor Kit	Optional	Optional	Optional
Coil Tine Track Remover	Standard	Standard	Standard
Lift Sling Kit	Optional	Optional	Optional
Electronic Acre Meter Kit	Optional	Optional	Optional
Brush Agitator Kit for Brome Box	Optional	Optional	Optional
Speed Up Kit (Doubles Output)	Optional	Optional	Optional
SMV Emblem	Standard	Standard	Standard
Powder Coat Paint, Red	Standard	Standard	Standard
Horsepower Requirements	35 HP (26.88 kW) and up	35 HP (26.88 kW) and up	35 HP (26.88 kW) and up
Recommended Operating Speed	3 to 5 MPH (5 to 8.3 km/h)	3 to 5 MPH (5 to 8.3 km/h)	3 to 5 MPH (5 to 8.3 km/h)