



Pulverizer Specifications

P Series - No Transport Models - 10 ft. to 16 ft.

Product Attributes	P10	P12	P14	P16
Approximate Weight				
(PDS) 20" Notched Ductile Iron Wheels with Scrapers	2,077 lbs. (942 kg)	2,371 lbs. (1,075 kg)	2,658 lbs. (1,206 kg)	2,961 lbs. (1,343 kg)
(PD) 20" Notched Ductile Iron Wheels Excluding Scrapers	1,952 lbs. (885 kg)	2,226 lbs. (1,010 kg)	2,501 lbs. (1,134 kg)	2,776 lbs. (1,259 kg)
(PC) 20" Crowfoot Ductile Iron Wheels	1,837 lbs. (833 kg)	2,090 lbs. (948 kg)	2,343 lbs. (1,063 kg)	2,596 lbs. (1,178 kg)
Working Width	10 ft. 0 in. (3.0 m)	12 ft. 0 in. (3.6 m)	14 ft. 0 in. (4.2 m)	16 ft. 0 in. (4.8 m)
Transport Width	11 ft. 0 in. (3.4 m)	13 ft. 2 in. (4.7 m)	15 ft. 2 in. (5.4 m)	17 ft. 2 in. (6.2 m)
Transport Height	3 ft. 0 in. (1.0 m)	3 ft. 0 in. (1.0 m)	3 ft. 0 in. (1.0 m)	3 ft. 0 in. (1.0 m)
Overall Length	15 ft. 0 in. (4.6 m)	15 ft. 0 in. (4.6 m)	15 ft. 0 in. (4.6 m)	15 ft. 0 in. (4.6 m)
Number of Pulverizer Wheels				
(PDS) 20" Notched Ductile Iron Wheels with Scrapers	30	36	42	48
(PD) 20" Notched Ductile Iron Wheels Excluding Scrapers	30	36	42	48
(PC) 20" Crowfoot Ductile Iron Wheels	20	24	28	32
Axle Size	8 in. (203 mm)	8 in. (203 mm)	8 in. (203 mm)	8 in. (203 mm)
Hitch	Pull-Type/No Transport	Pull-Type/No Transport	Pull-Type/No Transport	Pull-Type/No Transport
Scraper Kits	Optional for PD Series	Optional for PD Series	Optional for PD Series	Optional for PD Series
Hydraulic Transport Kit	Optional	Optional	Optional	Optional
LED Safety Warning Lights & SMV Emblem	Standard	Standard	Standard	Standard
Safety Chain Kit	Standard	Standard	Standard	Standard
Powder Coat Paint, Red	Standard	Standard	Standard	Standard
Horsepower Requirements	50 HP (40.3 kW) and up	50 HP (40.3 kW) and up	60 HP (44.8 kW) and up	60 HP (44.8 kW) and up
Recommended Operating Speed	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)