



# Pulverizer Specifications

## PP Series - Three-Point Hitch Models

Product Attributes	PP5	PP6	PP7	PP8	PP10	PP12	PP14	PP16	PP18	PP20
<b>Approximate Weight</b>										
(PPM) 16" Notched Gray Iron Wheels	709 lbs. (322 kg)	826 lbs. (375 kg)	943 lbs. (428 kg)	1,090 lbs. (494 kg)	N/A	N/A	N/A	N/A	N/A	N/A
(PPD) 20" Notched Ductile Iron Wheels	645 lbs. (293 kg)	749 lbs. (340 kg)	853 lbs. (387 kg)	987 lbs. (448 kg)	1,568 lbs. (706 kg)	1,792 lbs. (806 kg)	2,016 lbs. (907 kg)	2,386 lbs. (1,074 kg)	2,769 lbs. (1,246 kg)	3,026 lbs. (1,362 kg)
(PPC) 16" Crowfoot Gray Iron Wheels	677 lbs. (307 kg)	789 lbs. (358 kg)	900 lbs. (408 kg)	1,041 lbs. (472 kg)	N/A	N/A	N/A	N/A	N/A	N/A
(PPO) 20" Optimizer Ductile Iron Wheels	N/A	N/A	N/A	N/A	1,653 lbs. (744 kg)	1,997 lbs. (899 kg)	2,253 lbs. (1,014 kg)	2,607 lbs. (1,173 kg)	2,921 lbs. (1,314 kg)	3,216 lbs. (1,447 kg)
<b>Working Width</b>	5 ft. 0 in. (1.5 m)	6 ft. 0 in. (1.8 m)	7 ft. 0 in. (2.1 m)	8 ft. 0 in. (2.4 m)	10 ft. 0 in. (3.0 m)	12 ft. 0 in. (3.6 m)	14 ft. 0 in. (4.2 m)	16 ft. 0 in. (4.8 m)	18 ft. 0 in. (5.4 m)	20 ft. 0 in. (6 m)
<b>Transport Width</b>	5 ft. 8 in. (1.7 m)	6 ft. 8 in. (2.0 m)	7 ft. 8 in. (2.3 m)	8 ft. 8 in. (2.6 m)	11 ft. 2 in. (3.4 m)	13 ft. 2 in. (4.7 m)	15 ft. 2 in. (5.4 m)	17 ft. 2 in. (6.2 m)	19 ft. 2 in. (5.75 m)	21 ft. 2 in. (6.35 m)
<b>Transport Height</b>	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor
<b>Overall Length</b>	2 ft. 0 in. (600 mm)	2 ft. 0 in. (600 mm)	2 ft. 0 in. (600 mm)	2 ft. 0 in. (600 mm)	4 ft. 3 in. (1.27 m)	4 ft. 3 in. (1.27 m)	4 ft. 3 in. (1.27 m)	4 ft. 3 in. (1.27 m)	4 ft. 3 in. (1.27 m)	4 ft. 3 in. (1.27 m)
<b>Number of Pulverizer Wheels</b>										
(PPM) 16" Notched Gray Iron Wheels	15	18	21	24	N/A	N/A	N/A	N/A	N/A	N/A
(PPD) 20" Notched Ductile Iron Wheels	15	18	21	24	30	36	42	48	54	60
(PPC) 16" Crowfoot Gray Iron Wheels	10	12	14	16	N/A	N/A	N/A	N/A	N/A	N/A
(PPO) 20" Optimizer Ductile Iron Wheels	N/A	N/A	N/A	N/A	20	24	28	32	36	40
<b>Axle Size</b>										
(PPM) 16" Notched Gray Iron Wheels	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	N/A	N/A	N/A	N/A	N/A	N/A
(PPD) 20" Notched Ductile Iron Wheels	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4.5 in. (114 mm)	4.5 in. (114 mm)
(PPC) 16" Crowfoot Gray Iron Wheels	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	N/A	N/A	N/A	N/A	N/A	N/A
(PPO) 20" Optimizer Ductile Iron Wheels	N/A	N/A	N/A	N/A	4.5 in. (114 mm)	4.5 in. (114 mm)	4.5 in. (114 mm)	4.5 in. (114 mm)	4.5 in. (114 mm)	4.5 in. (114 mm)
<b>Three-Point Hitch</b>	Cat. I, II Free Link; Cat. I, II Quick Coupler	Cat. I, II Free Link; Cat. I, II Quick Coupler	Cat. I, II Free Link; Cat. I, II Quick Coupler	Cat. I, II Free Link; Cat. I, II Quick Coupler	Cat. II Free Link; Cat. II, IIIN Quick Coupler	Cat. II Free Link; Cat. II, IIIN Quick Coupler	Cat. II Free Link; Cat. II, IIIN Quick Coupler	Cat. II Free Link; Cat. II, IIIN Quick Coupler	Cat. II Free Link; Cat. II, IIIN Quick Coupler	Cat. II Free Link; Cat. II, IIIN Quick Coupler
<b>Pull-Type Hitch</b>	Optional	Optional	Optional	Optional	N/A	N/A	N/A	N/A	N/A	N/A
<b>Scraper Kits</b>	Optional for PPM & PPD Series	Optional for PPM & PPD Series	Optional for PPM & PPD Series	Optional for PPM & PPD Series	Optional for PPD Series	Optional for PPD Series	Optional for PPD Series	Optional for PPD Series	Optional for PPD Series	Optional for PPD Series
<b>S-Tine Track Remover Kit</b>	N/A	N/A	N/A	N/A	Optional	Optional	Optional	Optional	Optional	Optional
<b>Rear Hitch</b>	N/A	N/A	N/A	N/A	Optional	Optional	Optional	Optional	Optional	Optional
<b>LED Safety Warning Lights &amp; SMV Emblem</b>	SMV Emblem Only	SMV Emblem Only	SMV Emblem Only	SMV Emblem Only	Standard	Standard	Standard	Standard	Standard	Standard
<b>Powder Coat Paint, Red</b>	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>Horsepower Requirements</b>	35 HP (26.88 kW) and up	35 HP (26.88 kW) and up	45 HP (33.6 kW)	45 HP (33.6 kW)	60 HP (44.8 kW)	60 HP (44.8 kW)	75 HP (56 kW)	75 HP (56 kW)	90 HP (67.2 kW)	90 HP (67.2 kW)
<b>Recommended Operating Speed</b>	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)