



# Seedbed Mulch Tucker Specifications

Product Attributes	SMT-6	SMT-8	T-6	T-8
Approximate Weight	1,340 lbs. (603 kg)	1,600 lbs. (720 kg)	404 lbs. (182 kg)	491 lbs. (221 kg)
Working Width	6 ft. 0 in. (1.8 m)	8 ft. 0 in. (2.4 m)	6 ft. 0 in. (1.8 m)	8 ft. 0 in. (2.4 m)
Transport Width	6 ft. 8 in. (2.0 m)	8 ft. 8 in. (2.6 m)	6 ft. 8 in. (2.0 m)	8 ft. 8 in. (2.6 m)
Transport Height	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor
Road Clearance	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor
Overall Length	3 ft. 10 in. (1.15 m)	3 ft. 10 in. (1.15 m)	2 ft. 0 in. (0.61 m)	2 ft. 0 in. (0.61 m)
Frame Structure	4 in. x 4 in. (254 mm x 254 mm)	4 in. x 4 in. (254 mm x 254 mm)	4 in. x 4 in. (254 mm x 254 mm)	4 in. x 4 in. (254 mm x 254 mm)
Pulverizer Wheels	16 in. (406 mm) Notched Gray Iron	16 in. (406 mm) Notched Gray Iron	N/A	N/A
Number of Wheels	18	24	N/A	N/A
Axle Size - Pulverizer	4 in. (100 mm)	4 in. (100 mm)	N/A	N/A
Pulverizer Bearings	Triple Sealed	Triple Sealed	N/A	N/A
Tucker Wheels	20 in. x .1875 in. (508 mm x 47 mm)	20 in. x .1875 in. (508 mm x 47 mm)	20 in. x .1875 in. (508 mm x 47 mm)	20 in. x .1875 in. (508 mm x 47 mm)
Number of Tucker Wheels	9	12	9	12
Axle Size - Tucker	1.5 in. (38.1 mm) Square	1.5 in. (38.1 mm) Square	1.5 in. (38.1 mm) Square	1.5 in. (38.1 mm) Square
Tucker Bearings	Triple Sealed Self-Aligning	Triple Sealed Self-Aligning	Triple Sealed Self-Aligning	Triple Sealed Self-Aligning
Three-Point Hitch	Cat. I Free Link	Cat. I, II Free Link; Cat. I, II Quick Coupler Hitch	Cat. I Free Link	Cat. I, II Free Link; Cat. I, II Quick Coupler Hitch
SMV Emblem	Standard	Standard	Standard	Standard
Powder Coat Paint, Red	Standard	Standard	Standard	Standard
Horsepower Requirements	35 HP (26.88 kW) and up	45 HP (33.6 kW)	35 HP (26.88 kW) and up	45 HP (33.6 kW)
Recommended Operating Speed	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)