



2211 Series Ripoll Specifications

Chopper Reel Attachment

| Adapts To: | 2211-9 | 2211-11 | 2211-13 | 2211-15 |
|----------------------------|---|---|---|---|
| Approximate Weight | 1,738 lbs. (788 kg) | 1,768 lbs. (802 kg) | 2,540 lbs. (1,152 kg) | 2,540 lbs. (1,152 kg) |
| Chopper Reel | 5-Blade, 16 in. (406 mm) Diameter | 5-Blade, 16 in. (406 mm) Diameter | 5-Blade, 16 in. (406 mm) Diameter | 5-Blade, 16 in. (406 mm) Diameter |
| Reel Blades | 0.281 in. x 4 in. (7.1 x 102 mm) Beveled | 0.281 in. x 4 in. (7.1 x 102 mm) Beveled | 0.281 in. x 4 in. (7.1 x 102 mm) Beveled | 0.281 in. x 4 in. (7.1 x 102 mm) Beveled |
| Reel Bearings | C-Cushion Trunnion Mount, Greaseable Triple Lip Seals | C-Cushion Trunnion Mount, Greaseable Triple Lip Seals | C-Cushion Trunnion Mount, Greaseable Triple Lip Seals | C-Cushion Trunnion Mount, Greaseable Triple Lip Seals |
| Reel Protection | Individual Arm Mounted Adjustable Springs with C-Flex | Individual Arm Mounted Adjustable Springs with C-Flex | Individual Arm Mounted Adjustable Springs with C-Flex | Individual Arm Mounted Adjustable Springs with C-Flex |
| Number of Reels | 2 | 2 | 2 | 2 |
| Number of Mounting Arms | 4 | 4 | 6 | 6 |
| Independent Hydraulic Lift | Optional | Optional | Optional | Optional |