



**A LANDOLL PRODUCT**

# Agricultural Seeder Specifications

## SS-16 Models

Product Attributes	SSP16	SS16
Approximate Weight	5,519 lbs. (2,503 kg)	6,757 lbs. (3,065 kg)
Working Width	16 ft. 0 in. (4.8 m)	16 ft. 0 in. (4.8 m)
Transport Width	17 ft. 6 in. (5.3 m)	17 ft. 6 in. (5.3 m)
Transport Height	Tractor Dependent	6 ft. 0 in. (1.8 m)
Transport Length	Tractor Dependent	16 ft. 2 in. (4.9 m)
Road Clearance	Tractor Dependent	13 in. (330 mm)
Working Overall Height	4 ft. 9 in. (1.4 m)	4 ft. 9 in. (1.4 m)
Working Overall Length	5 ft. 11 in. (1.8 m)	17 ft. 0 in. (5.2 m)
Seed Box	All Steel Construction with Cover	All Steel Construction with Cover
Seed Box Capacity (Micro-Meter)	20 bu.	20 bu.
Seed Meters	"Micro-Meter"	"Micro-Meter"
Seed Meter Drive	Ground Driven	Ground Driven
Seed Meter/Opening Spacing	8 in. (203 mm)	8 in. (203 mm)
Seed Delivery	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray
Pulverizer Roller - Front	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron
Pulverizer Roller - Rear	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron
Pulverizer Axle Bearings	1.75 in. (45 mm) Flange Bearing Sealed	1.75 in. (45 mm) Flange Bearing Sealed
Pulverizer Axle Size - Front	12.75 in. (324 mm)	12.75 in. (324 mm)
Pulverizer Axle Size - Rear	8.625 in. (219 mm)	8.625 in. (219 mm)
Hitch Type	Three-Point Hitch	Drawbar with Hydraulic Transport
Hitch Category	Cat. II, III Free Link; Cat. II, IIIN, III Quick Coupler Hitch	Cat. II, III
Tire Size	N/A	(4) 11L x 15, 12 Ply Implement Rib
S-Tine Wheel Track Remover	Optional	Optional
Coil Tine Wheel Track Remover	Optional	Optional
Electronic Acre Meter	Optional	Optional
Electric Clutch with Seed Shaft Sensor and Monitor	Optional	Optional
Seed Box Scale System	Optional	Optional
Safety Warning Lights & SMV Emblem	Standard	Standard
Safety Chain Kit	N/A	Standard
Powder Coat Paint, Red	Standard	Standard
Horsepower Requirements	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.
Required Three-Point Hitch Lift Capacity	6,719 lbs. (3,048 kg) Minimum	N/A
Recommended Operating Speed	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions