



# 2100 Series Coulter Chisel Specifications

Chopper Reels for Auto-Reset Shanks

Adapts To:	2110-7	2110-9	2111-11	2111-13	2111-15	2131-15	2131-17	2131-19	2131-21	2131-23	2131-25
<b>Approximate Weight</b>	914 lbs. (415 kg)	1,694 lbs. (768 kg)	1,754 lbs. (796 kg)	1,930 lbs. (875 kg)	2,390 lbs. (1,084 kg)	N/A	2,992 lbs. (1,357 kg)	3,344 lbs. (1,517 kg)	3,696 lbs. (1,676 kg)	4,048 lbs. (1,836 kg)	4,358 lbs. (1,977 kg)
<b>Chopper Reel</b>	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	N/A	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
<b>Reel Blades</b>	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	N/A	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled
<b>Reel Bearings</b>	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	N/A	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
<b>Reel Protection</b>	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	N/A	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex
<b>Number of Reels</b>	1	2	2	2	2	N/A	3	3	3	3	3
<b>Independent Hydraulic Lift</b>	Optional	Optional	Optional	Optional	Optional	N/A	Optional	Optional	Optional	Optional	Optional
<b>Weight Kit Required</b>	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	N/A	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed