



Zone Commander Specifications

Auto-Reset Spring Shanks - Non-Folding Units

Product Attributes	2511ZC-3N	2511ZC-4N	2511ZC-5N	2512ZC-5	2512ZC-6	2512ZC-7
Approximate Weight	3,357 lbs. (1,523 kg)	3,849 lbs. (1,746 kg)	4,725 lbs. (2,143 kg)	6,398 lbs. (2,902 kg)	8,209 lbs. (3,724 kg)	9,406 lbs. (4,266 kg)
Working Width	7 ft. 6 in. (2.3 m)	10 ft. 0 in. (3.0 m)	12 ft. 6 in. (3.8 m)	12 ft. 6 in. (3.8 m)	15 ft. 0 in. (4.6 m)	17 ft. 6 in. (5.3 m)
Transport Width	9 ft. 3 in. (2.8 m)	9 ft. 3 in. (2.8 m)	12 ft. 0 in. (3.7 m)	11 ft. 6 in. (3.5 m)	13 ft. 5 in. (4.1 m)	15 ft. 11 in. (4.9 m)
Frame Type	Narrow Non-Folding	Narrow Non-Folding	Narrow Non-Folding	Standard Non-Folding	Standard Non-Folding	Standard Non-Folding
Frame Structure	6 in. x 4 in. (152 x 102 mm) Double Bar Frame	6 in. x 4 in. (152 x 102 mm) Double Bar Frame	6 in. x 4 in. (152 x 102 mm) Double Bar Frame	6 in. x 6 in. x 0.5 in. (152 x 152 x 13 mm) Rear Frame 6 in. x 4 in. x 0.5 in. (152 x 102 x 13 mm) Front Frame	6 in. x 6 in. x 0.5 in. (152 x 152 x 13 mm) Rear Frame 6 in. x 4 in. x 0.5 in. (152 x 102 x 13 mm) Front Frame	6 in. x 6 in. x 0.5 in. (152 x 152 x 13 mm) Rear Frame 6 in. x 4 in. x 0.5 in. (152 x 102 x 13 mm) Front Frame
Frame Construction	Laser Cut Components; Robotically Welded	Laser Cut Components; Robotically Welded	Laser Cut Components; Robotically Welded	Laser Cut Components; Robotically Welded	Laser Cut Components; Robotically Welded	Laser Cut Components; Robotically Welded
Frame Extensions	None	None	12 in. (305 mm) Bolt-On	None	12 in. (305 mm) Bolt-On	27 in. (686 mm) Bolt-On
Coulter Assemblies	Standard	Standard	Standard	Standard	Standard	Standard
Number of Coulters	3	4	5	5	6	7
Coulter Blade Diameter	22 in. (559 mm) Smooth Blade (Standard)	22 in. (559 mm) Smooth Blade (Standard)	22 in. (559 mm) Smooth Blade (Standard)	22 in. (559 mm) Smooth Blade (Standard)	22 in. (559 mm) Smooth Blade (Standard)	22 in. (559 mm) Smooth Blade (Standard)
Coulter Protection	Adjustable Spring Cushion	Adjustable Spring Cushion	Adjustable Spring Cushion	Adjustable Spring Cushion	Adjustable Spring Cushion	Adjustable Spring Cushion
Coulter Down Pressure	600 lbs. (272 kg)	600 lbs. (272 kg)	600 lbs. (272 kg)	600 lbs. (272 kg)	600 lbs. (272 kg)	600 lbs. (272 kg)
Coulter Trip Height	6 in. (152 mm)	6 in. (152 mm)	6 in. (152 mm)	6 in. (152 mm)	6 in. (152 mm)	6 in. (152 mm)
22 in. Ripple Coulter	Optional	Optional	Optional	Optional	Optional	Optional
22 in. Pyramid Coulter	Optional	Optional	Optional	Optional	Optional	Optional
Number of Shanks	3	4	5	5	6	7
Shank Type	Auto-Reset Spring Shank	Auto-Reset Spring Shank	Auto-Reset Spring Shank	Auto-Reset Spring Shank	Auto-Reset Spring Shank	Auto-Reset Spring Shank
Shank Leg Type*	1.25 in. x 5 in. x 36 in. (32.8 x 127 x 914 mm) Straight Leg Shank 1.25 in. x 4 in. x 36 in. (32.8 x 102 x 914 mm) Parabolic Shank 0.75 in. x 5 in. x 32 in. (19 x 127 x 813 mm) Low Disturbance Shank	1.25 in. x 5 in. x 36 in. (32.8 x 127 x 914 mm) Straight Leg Shank 1.25 in. x 4 in. x 36 in. (32.8 x 102 x 914 mm) Parabolic Shank 0.75 in. x 5 in. x 32 in. (19 x 127 x 813 mm) Low Disturbance Shank	1.25 in. x 5 in. x 36 in. (32.8 x 127 x 914 mm) Straight Leg Shank 1.25 in. x 4 in. x 36 in. (32.8 x 102 x 914 mm) Parabolic Shank 0.75 in. x 5 in. x 32 in. (19 x 127 x 813 mm) Low Disturbance Shank	1.25 in. x 5 in. x 36 in. (32.8 x 127 x 914 mm) Straight Leg Shank 1.25 in. x 4 in. x 36 in. (32.8 x 102 x 914 mm) Parabolic Shank 0.75 in. x 5 in. x 32 in. (19 x 127 x 813 mm) Low Disturbance Shank	1.25 in. x 5 in. x 36 in. (32.8 x 127 x 914 mm) Straight Leg Shank 1.25 in. x 4 in. x 36 in. (32.8 x 102 x 914 mm) Parabolic Shank 0.75 in. x 5 in. x 32 in. (19 x 127 x 813 mm) Low Disturbance Shank	1.25 in. x 5 in. x 36 in. (32.8 x 127 x 914 mm) Straight Leg Shank 1.25 in. x 4 in. x 36 in. (32.8 x 102 x 914 mm) Parabolic Shank 0.75 in. x 5 in. x 32 in. (19 x 127 x 813 mm) Low Disturbance Shank
Shank Spacing	30 in. (762 mm)	30 in. (762 mm)	30 in. (762 mm)	30 in. (762 mm)	30 in. (762 mm)	30 in. (762 mm)
Maximum Shank Working Depth	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)
Shank Trip Height	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)	16 in. (406 mm)
Point Load	2,300 lbs. (1,043 kg)	2,300 lbs. (1,043 kg)	2,300 lbs. (1,043 kg)	2,300 lbs. (1,043 kg)	2,300 lbs. (1,043 kg)	2,300 lbs. (1,043 kg)
Under Frame Clearance	40.5 in. (1.0 m)	40.5 in. (1.0 m)	40.5 in. (1.0 m)	40.5 in. (1.0 m)	40.5 in. (1.0 m)	40.5 in. (1.0 m)

*Units are equipped with choice of Straight Leg Shanks, Parabolic Shanks or Low Disturbance Shanks. Points and Wearstrips listed as Standard are included with each respective shank choice, unless Optional equipment is chosen.



Zone Commander Specifications

Auto-Reset Spring Shanks - Non-Folding Units

Product Attributes	2511ZC-3N	2511ZC-4N	2511ZC-5N	2512ZC-5	2512ZC-6	2512ZC-7	
Points for Straight Leg Shanks	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)
Wearstrips for Straight Leg Shanks	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	
Points for Parabolic Shanks	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)	2.5 in. (63.5 mm) C.A.D.I. Point (Standard) 2.375 in. (60.3 mm) Shark Fin C.A.D.I. Point (Optional) 7 in. (178 mm) Wing Point w/Cast Cap (Optional) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional) 10 in. (254 mm) Wing Point w/Chrome Cap (Optional)
Wearstrips for Parabolic Shanks	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	
Points for Low Disturbance Shanks	2 in. (50.8 mm) V-Shaped Point (Standard) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional)	2 in. (50.8 mm) V-Shaped Point (Standard) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional)	2 in. (50.8 mm) V-Shaped Point (Standard) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional)	2 in. (50.8 mm) V-Shaped Point (Standard) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional)	2 in. (50.8 mm) V-Shaped Point (Standard) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional)	2 in. (50.8 mm) V-Shaped Point (Standard) 7 in. (178 mm) Wing Point w/Chrome Cap (Optional)	
Wearstrips for Low Disturbance Shanks	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	C.A.D.I. Wearstrip (Standard)	
Gauge Wheels	(2) Standard	(2) Standard	(2) Standard	(2) Standard	(2) Standard	(2) Standard	
Gauge Wheel Type	Turnbuckle Adjustable	Turnbuckle Adjustable	Turnbuckle Adjustable	Turnbuckle Adjustable	Turnbuckle Adjustable	Turnbuckle Adjustable	
Gauge Wheel Hubs	6-Bolt	6-Bolt	6-Bolt	6-Bolt	6-Bolt	6-Bolt	
Gauge Wheel Tire Size	HD 280/70R x 15	HD 280/70R x 15	HD 280/70R x 15	HD 280/70R x 15	HD 280/70R x 15	HD 280/70R x 15	
Three-Point Hitch	Cat. II, IIIN	Cat. II, IIIN	Cat. II, IIIN	Cat. III, IV	Cat. III, IV	Cat. III, IV	
Coverboard Kit	Optional	Optional	Optional	Optional	Optional	Optional	
12 in. Offset Shank Mounts	Optional	Optional	Optional	Optional	Optional	Optional	
Pull-Hitch Caddy	N/A	N/A	N/A	Optional	Optional	Optional	
Rear Hitch	N/A	Optional	Optional	Optional	Optional	Optional	
Parking Stands	Standard	Standard	Standard	Standard	Standard	Standard	
Powder Coat Paint, Red	Standard	Standard	Standard	Standard	Standard	Standard	
LED Warning Lights & SMV Emblem	Standard	Standard	Standard	Standard	Standard	Standard	
Horsepower Requirements	40 HP and up (30 kW) Per Shank	40 HP and up (30 kW) Per Shank	40 HP and up (30 kW) Per Shank	40 HP and up (30 kW) Per Shank	40 HP and up (30 kW) Per Shank	40 HP and up (30 kW) Per Shank	
Recommended Operating Speed	3 to 5 MPH (4.8 to 8.0 km/h)	3 to 5 MPH (4.8 to 8.0 km/h)	3 to 5 MPH (4.8 to 8.0 km/h)	3 to 5 MPH (4.8 to 8.0 km/h)	3 to 5 MPH (4.8 to 8.0 km/h)	3 to 5 MPH (4.8 to 8.0 km/h)	

*Units are equipped with choice of Straight Leg Shanks, Parabolic Shanks or Low Disturbance Shanks. Points and Wearstrips listed as Standard are included with each respective shank choice, unless Optional equipment is chosen.