



# 9600 Series Field Cultivator Specifications

Flexible Five Row Spike Harrow

## 9630 Three-Section Folding Models

Adapts To:	9630-20	9630-24	9630-28	9630-30NC
Approximate Weight	2,042 lbs. (926 kg)	2,160 lbs. (980 kg)	2,675 lbs. (1,213 kg)	2,789 lbs. (1,265 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	6 ft. (1.8 m) -- 10.5 ft. (3.2 m) -- 6 ft. (1.8 m)	7.5 ft. (2.3 m) -- 11.25 ft. (3.4 m) -- 7.5 ft. (2.3 m)	9.75 ft. (3.0 m) -- 10.5 ft. (3.2 m) -- 9.75 ft. (3.0 m)	10.5 ft. (3.2 m) -- 11.25 ft. (3.4 m) -- 10.5 ft. (3.2 m)

Adapts To:	9630-30/9630-30FH	9630-32/9630-32FH	9630-34/9630-34FH
Approximate Weight	2,921 lbs. (1,324 kg)	2,980 lbs. (1,352 kg)	3,100 lbs. (1,406 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	9.75 ft. (3.0 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 9.75 ft. (3.0 m)	10.5 ft. (3.2 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 10.5 ft. (3.2 m)	12 ft. (3.7 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 12 ft. (3.7 m)

## 9650 Five-Section Folding Models

Adapts To:	9650-38/9650-38FH	9650-42/9650-42FH
Approximate Weight	3,742 lbs. (1,697 kg)	3,857 lbs. (1,750 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	6 ft. (1.8 m) -- 8.25 ft. (2.5 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 8.25 ft. (2.5 m) -- 6 ft. (1.8 m)	7.5 ft. (2.3 m) -- 8.25 ft. (2.5 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 8.25 ft. (2.5 m) -- 7.5 ft. (2.3 m)

Adapts To:	9650-46/9650-46FH	9650-50/9650-50FH
Approximate Weight	4,034 lbs. (1,830 kg)	4,151 lbs. (1,883 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	8.25 ft. (2.5 m) -- 9.75 ft. (3.0 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 9.75 ft. (3.0 m) -- 8.25 ft. (2.5 m)	9.75 ft. (3.0 m) -- 9.75 ft. (3.0 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 9.75 ft. (3.0 m) -- 9.75 ft. (3.0 m)