



# 9600 Series Field Cultivator Specifications

## Three Row Spike and Reel

### 9630 Three-Section Folding Models

Adapts To:	9630-20	9630-24	9630-28	9630-30NC
Approximate Weight	2,777 lbs. (2,777 kg)	2,943 lbs. (1,335 kg)	3,502 lbs. (1,588 kg)	3,539 lbs. (1,605 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional	Optional
Section Sizes	6.25 ft. (1.9 m) -- 8.75 ft. (2.7 m) -- 6.25 ft. (1.9 m)	7.5 ft. (2.3 m) -- 10 ft. (3.0 m) -- 7.5 ft. (2.3 m)	10 ft. (3.0 m) -- 8.75 ft. (2.7 m) -- 10 ft. (3.0 m)	10.5 ft. (3.2 m) -- 11.25 ft. (3.4 m) -- 10.5 ft. (3.2 m)

Adapts To:	9630-30/9630-30FH	9630-32/9630-32FH	9630-34/9630-34FH
Approximate Weight	3,582 lbs. (1,625 kg)	3,983 lbs. (1,807 kg)	4,070 lbs. (1,846 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional
Section Sizes	8.75 ft. (2.7 m) -- 6.25 ft. (1.9 m) -- 6.25 ft. (1.9 m) -- 8.75 ft. (2.7 m)	9.75 ft. (3.0 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m) -- 9.75 ft. (3.0 m)	10 ft. (3.0 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m) -- 10 ft. (3.0 m)

### 9650 Five-Section Folding Models

Adapts To:	9650-38/9650-38FH	9650-42/9650-42FH
Approximate Weight	4,995 lbs. (2,266 kg)	5,189 lbs. (2,354 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional
Section Sizes	5 ft. (1.5 m) -- 7.5 ft. (2.3 m) -- 6.25 ft. (1.9 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m) -- 5 ft. (1.5 m)	7.5 ft. (2.3 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m) -- 7.5 ft. (2.3 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m)

Adapts To:	9650-46/9650-46FH	9650-50/9650-50FH
Approximate Weight	5,749 lbs. (2,608 kg)	5,943 lbs. (2,696 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional
Section Sizes	7.5 ft. (2.3 m) -- 8.75 ft. (2.7 m) -- 6.25 ft. (1.9 m) -- 6.25 ft. (1.9 m) -- 8.75 ft. (2.7 m) -- 7.5 ft. (2.3 m)	8.75 ft. (2.7 m) -- 8.75 ft. (2.7 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m) -- 8.75 ft. (2.7 m) -- 8.75 ft. (2.7 m)