



9600 Series Field Cultivator Specifications

Three Row Tine and Reel

9630 Three-Section Folding Models

Adapts To:	9630-20	9630-24	9630-28	9630-30NC
Approximate Weight	3,282 lbs. (1,489 kg)	3,487 lbs. (1,582 kg)	3,705 lbs. (1,681 kg)	3,763 lbs. (1,707 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Tine Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional	Optional
Section Sizes	6.25 ft. (1.9 m) -- 8.75 ft. (2.7 m) -- 6.25 ft. (1.9 m)	7.5 ft. (2.3 m) -- 10 ft. (3.0 m) -- 7.5 ft. (2.3 m)	10 ft. (3.0 m) -- 8.75 ft. (2.7 m) -- 10 ft. (3.0 m)	10.5 ft. (3.2 m) -- 10.5 ft. (3.2 m) -- 10.5 ft. (3.2 m)

Adapts To:	9630-30/9630-30FH	9630-32/9630-32FH	9630-34/9630-34FH
Approximate Weight	4,377 lbs. (1,985 kg)	4,538 lbs. (2,058 kg)	5,181 lbs. (2,350 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Tine Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional
Section Sizes	8.75 ft. (2.7 m) -- 6.25 ft. (1.9 m) -- 6.25 ft. (1.9 m) -- 8.75 ft. (2.7 m)	8.75 ft. (2.7 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m) -- 8.75 ft. (2.7 m)	10 ft. (3.0 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m) -- 10 ft. (3.0 m)

9650 Five-Section Folding Models

Adapts To:	9650-38/9650-38FH	9650-42/9650-42FH
Approximate Weight	6,307 lbs. (2,861 kg)	6,531 lbs. (2,962 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Tine Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional
Section Sizes	7 ft. (2.1 m) -- 8 ft. (2.4 m) -- 12 ft. (3.7 m) -- 8 ft. (2.4 m) -- 7 ft. (2.1 m)	8 ft. (2.4 m) -- 8 ft. (2.4 m) -- 12 ft. (3.7 m) -- 8 ft. (2.4 m) -- 8 ft. (2.4 m)

Adapts To:	9650-46/9650-46FH	9650-50/9650-50FH
Approximate Weight	6,610 lbs. (2,998 kg)	6,913 lbs. (3,136 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Tine Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional
Section Sizes	8 ft. (2.4 m) -- 9 ft. (2.7 m) -- 13 ft. (4.0 m) -- 9 ft. (2.7 m) -- 8 ft. (2.4 m)	9 ft. (2.7 m) -- 9 ft. (2.7 m) -- 7 ft. (2.1 m) -- 8 ft. (2.4 m) -- 9 ft. (2.7 m) -- 9 ft. (2.7 m)