



Power Ditcher Specifications

Product Attributes	D5P18A	D10P18A	D10PH18A
Approximate Weight	525 lbs. (238 kg)	525 lbs. (238 kg)	530 lbs. (240 kg)
PTO RPM	540 RPM	1,000 RPM	1,000 RPM
PTO Coupler Size	1.375 in. (34.9 mm)	1.375 in. (34.9 mm)	1.75 in. (44.5 mm)
Shear Bolt Size	0.375 in. (9.5 mm)	0.375 in. (9.5 mm)	0.375 in. (9.5 mm)
Cutter Head Speed	740 RPM	740 RPM	740 RPM
Adjustable Cutter Head	18 in. to 20 in. (458 to 508 mm)	18 in. to 20 in. (458 to 508 mm)	18 in. to 20 in. (458 to 508 mm)
Cutter Blades	(4) Replaceable Heat Treated	(4) Replaceable Heat Treated	(4) Replaceable Heat Treated
Chain Case	6 in. x 10 in. (152 x 254 mm)	6 in. x 10 in. (152 x 254 mm)	6 in. x 10 in. (152 x 254 mm)
Chain	Double #80	Double #80	Double #80
Sprockets	16 and 22 Tooth Hardened	16 and 22 Tooth Hardened	16 and 22 Tooth Hardened
Three-Point Hitch	Cat. II, III or Quick Hitch	Cat. II, III or Quick Hitch	Cat. II, III or Quick Hitch
Depth of Operation	Depth Skid and Three-Point Adjustable	Depth Skid and Three-Point Adjustable	Depth Skid and Three-Point Adjustable
Parking Stands	(2) Standard	(2) Standard	(2) Standard
Powder Coat Paint, Sapphire Blue	Standard	Standard	Standard
Horsepower Requirements	50 to 100 HP (37 to 75 kW)	80 to 150 HP (60 to 112 kW)	80 to 150 HP (60 to 112 kW)