

8500 Series Finisholl Specifications Chopper, Two Row Spike and Reel

Adapts To:	8530-27	8530-30
Approximate Weight	5,960 lbs. (2,703 kg)	6,550 lbs. (2,971 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 5 in. (127 mm) Spacing	Overall 5 in. (127 mm) Spacing
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Flat Blade	Flat Blade
Section Sizes	N/A	N/A

Adapts To:	8530-33	8530-35
Approximate Weight	7,205 lbs. (3,268 kg)	7,640 lbs. (3,465 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 5 in. (127 mm) Spacing	Overall 5 in. (127 mm) Spacing
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Flat Blade	Flat Blade
Section Sizes	10 ft. (3.0 m) 6.25 ft. (1.9 m) 6.25 ft. (1.9 m) 10 ft. (3.0 m)	10 ft. (3.0 m) 7.5 ft. (2.3 m) 7.5 ft. (2.3 m) 10 ft. (3.0 m)

Adapts To:	8550-38	8550-43
Approximate Weight	8,347 lbs. (3,786 kg)	9,440 lbs. (4,282 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 5 in. (127 mm) Spacing	Overall 5 in. (127 mm) Spacing
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Flat Blade	Flat Blade
Section Sizes	6.25 ft. (1.9 m)	7.5 ft. (2.3 m) 7.5 ft. (2.3 m) 6.25 ft. (1.9 m) 6.25 ft. (1.9 m) 7.5 ft. (2.3 m) 7.5 ft. (2.3 m)

Revised 8/18/2022 Specifications subject to change with or without notice.