



8500 Series Finishroll Specifications

Chopper and Three Row Spike Drag

Adapts To:	8530-19	8530-22	8530-25
Approximate Weight	3,459 lbs. (1,569 kg)	3,661 lbs. (1,661 kg)	3,770 lbs. (1,710 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 3 in. (76.2 mm) Spacing	Overall 3 in. (76.2 mm) Spacing	Overall 3 in. (76.2 mm) Spacing
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	6 ft. (1.8 m) -- 9 ft. (2.7 m) -- 6 ft. (1.8 m)	7.5 ft. (2.3 m) -- 9 ft. (2.7 m) -- 7.5 ft. (2.3 m)	8.25 ft. (2.5 m) -- 9.75 ft. (3.0 m) -- 8.25 ft. (2.5 m)

Adapts To:	8530-27	8530-30	8530-33
Approximate Weight	4,146 lbs. (1,881 kg)	4,790 lbs. (2,173 kg)	5,512 lbs. (2,500 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 3 in. (76.2 mm) Spacing	Overall 3 in. (76.2 mm) Spacing	Overall 3 in. (76.2 mm) Spacing
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	8.25 ft. (2.5 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 8.25 ft. (2.5 m)	9.75 ft. (3.0 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 9.75 ft. (3.0 m)	10.5 ft. (3.2 m) -- 6.75 ft. (2.1 m) -- 6.75 ft. (2.1 m) -- 10.5 ft. (3.2 m)

Adapts To:	8530-35	8550-38
Approximate Weight	5,640 lbs. (2,558 kg)	6,235 lbs. (2,828 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 3 in. (76.2 mm) Spacing	Overall 3 in. (76.2 mm) Spacing
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	11.25 ft. (3.4 m) -- 6.75 ft. (2.1 m) -- 7.5 ft. (2.3 m) -- 11.75 ft. (3.6 m)	6 ft. (1.8 m) -- 7.5 ft. (2.3 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 7.5 ft. (2.3 m) -- 6 ft. (1.8 m)

Adapts To:	8550-43	8550-48
Approximate Weight	6,510 lbs. (2,953 kg)	6,950 lbs. (3,152 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 3 in. (76.2 mm) Spacing	Overall 3 in. (76.2 mm) Spacing
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	7.5 ft. (2.3 m) -- 8.25 ft. (2.5 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 8.25 ft. (2.5 m) -- 7.5 ft. (2.3 m)	9.75 ft. (3.0 m) -- 9 ft. (2.7 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 9 ft. (2.7 m) -- 9.75 ft. (3.0 m)