



8500 Series Finisholl Specifications

Flexible Five Row Spike Harrow

Adapts To:	8530-19	8530-22
Approximate Weight	1,980 lbs. (898 kg)	2,295 lbs. (1,041 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	6 ft. (1.8 m) -- 9 ft. (2.7 m) -- 6 ft. (1.8 m)	7.5 ft. (2.3 m) -- 9 ft. (2.7 m) -- 7.5 ft. (2.3 m)

Adapts To:	8530-25	8530-27
Approximate Weight	2,360 lbs. (1,070 kg)	2,675 lbs. (1,213 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	8.25 ft. (2.5 m) -- 9.75 ft. (3.0 m) -- 8.25 ft. (2.5 m)	8.25 ft. (2.5 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 8.25 ft. (2.5 m)

Adapts To:	8530-30	8530-33
Approximate Weight	2,790 lbs. (1,266 kg)	2,870 lbs. (1,302 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	9.75 ft. (3.0 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 9.75 ft. (3.0 m)	10.5 ft. (3.2 m) -- 6.75 ft. (2.1 m) -- 6.75 ft. (2.1 m) -- 10.5 ft. (3.2 m)

Adapts To:	8530-35	8550-38
Approximate Weight	2,990 lbs. (1,356 kg)	3,702 lbs. (1,679 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	11.25 ft. (3.4 m) -- 6.75 ft. (2.1 m) -- 7.5 ft. (2.3 m) -- 11.75 ft. (3.6 m)	6 ft. (1.8 m) -- 7.5 ft. (2.3 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 7.5 ft. (2.3 m) -- 6 ft. (1.8 m)

Adapts To:	8550-43	8550-48
Approximate Weight	3,880 lbs. (1,760 kg)	4,180 lbs. (1,896 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	1.8 in. (45.7 mm)	1.8 in. (45.7 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Section Sizes	7.5 ft. (2.3 m) -- 8.25 ft. (2.5 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 8.25 ft. (2.5 m) -- 7.5 ft. (2.3 m)	9.75 ft. (3.0 m) -- 9 ft. (2.7 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 9 ft. (2.7 m) -- 9.75 ft. (3.0 m)