



# 8500 Series Finisholl Specifications

Three Row Tine and Reel

Adapts To:	8530-19	8530-22	8530-25
Approximate Weight	3,210 lbs. (1,456 kg)	3,350 lbs. (1,520 kg)	3,492 lbs. (1,584 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Tine Adjustment	Multiple Angle Adjustments	Multiple Angle Adjustments	Multiple Angle Adjustments
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional
Section Sizes	6 ft. (1.8 m) -- 8 ft. (2.4 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 8 ft. (2.4 m) -- 8 ft. (2.4 m)	9 ft. (2.7 m) -- 8 ft. (2.4 m) -- 9 ft. (2.7 m)

Adapts To:	8530-27	8530-30	8530-33
Approximate Weight	4,326 lbs. (1,962 kg)	4,470 lbs. (2,028 kg)	4,607 lbs. (2,090 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Tine Adjustment	Multiple Angle Adjustments	Multiple Angle Adjustments	Multiple Angle Adjustments
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional
Section Sizes	8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m)	9 ft. (2.7 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 9 ft. (2.7 m)	9 ft. (2.7 m) -- 8 ft. (2.4 m) -- 8 ft. (2.4 m) -- 9 ft. (2.7 m)

Adapts To:	8530-35	8550-38	8550-43
Approximate Weight	4,741 lbs. (2,150 kg)	6,283 lbs. (2,850 kg)	6,559 lbs. (2,975 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Tine Adjustment	Multiple Angle Adjustments	Multiple Angle Adjustments	Multiple Angle Adjustments
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional
Section Sizes	10 ft. (3.0 m) -- 8 ft. (2.4 m) -- 8 ft. (2.4 m) -- 10 ft. (3.0 m)	6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m) -- 8 ft. (2.4 m)

Adapts To:	8550-48
Approximate Weight	6,845 lbs. (3,105 kg)
Tines	0.4375 in. x 18 in. (11.1 x 457 mm)
Tine Spacing	2.67 in. (67.8 mm)
Distance Between Bars	14 in. (356 mm)
Tine Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional
Section Sizes	9 ft. (2.7 m) -- 9 ft. (2.7 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 9 ft. (2.7 m) -- 9 ft. (2.7 m)