



2400 Series Weatherproofer (WP1) Specifications

Chopper Reel Attachment

| Adapts To:                 | 2411-6-24  | 2411AFG-7-24  | 2411AFG-9-24   | 2431-11-24  | 2431-13-24  |
|----------------------------|--|---|--|---|---|
| Approximate Weight         | 1,430 lbs. (649 kg)                                      | 1,680 lbs. (762 kg)   | 2,485 lbs. (1,127 kg)  | 2,683 lbs. (1,217 kg)   | 2,702 lbs. (1,226 kg)   |
| Chopper Reel               | 5-Blade, 16 in. (406 mm) Diameter                        | 5-Blade, 16 in. (406 mm) Diameter                                       | 5-Blade, 16 in. (406 mm) Diameter                                    | 5-Blade, 16 in. (406 mm) Diameter                                     | 5-Blade, 16 in. (406 mm) Diameter                                     |
| Reel Bearings              | C-Cushion Trunnion Mount,<br>Greaseable Triple Lip Seals | C-Cushion Trunnion Mount,<br>Greaseable Triple Lip Seals                | C-Cushion Trunnion Mount,<br>Greaseable Triple Lip Seals             | C-Cushion Trunnion Mount,<br>Greaseable Triple Lip Seals              | C-Cushion Trunnion Mount,<br>Greaseable Triple Lip Seals              |
| Reel Protection            | Individual Arm Mounted<br>Adjustable Springs with C-Flex | Individual Arm Mounted<br>Adjustable Springs with C-Flex                | Individual Arm Mounted<br>Adjustable Springs with C-Flex             | Individual Arm Mounted<br>Adjustable Springs with C-Flex              | Individual Arm Mounted<br>Adjustable Springs with C-Flex              |
| Independent Hydraulic Lift | Standard   | Standard  | Standard   | Standard  | Standard  |
| Section Width              | 8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m)               | 6 ft. 10 in. (2.1 m) -- 6 ft. 10 in. (2.1 m) --<br>6 ft. 10 in. (2.1 m) | 8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m) --<br>8 ft. 1 in. (2.5 m) | 7 ft. 7 in. (2.3 m) -- 10 ft. 9 in. (3.3 m) --<br>7 ft. 7 in. (2.3 m) | 9 ft. 6 in. (2.9 m) -- 10 ft. 9 in. (3.3 m) --<br>9 ft. 6 in. (2.9 m) |