



2400 Series Weatherproofer (WP1) Specifications

Combo Tine and Chopper Attachment

Adapts To:	2411-6-24	2411AFG-7-24	2411AFG-9-24	2431-11-24	2431-13-24
Approximate Weight	2,880 lbs. (1,306 kg)	3,740 lbs. (1,696 kg)	4,674 lbs. (2,120 kg)	4,746 lbs. (2,153 kg)	4,915 lbs. (2,229 kg)
Tines	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Reel Protection	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex
Independent Hydraulic Lift	Standard	Standard	Standard	Standard	Standard
Section Width	8 ft. (1.8 m) – 8 ft. (1.8 m)	6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m)	6 ft. (1.8 m) -- 14 ft. (4.3 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 14 ft. (4.3 m) -- 8 ft. (1.8 m)