



2400 Series Weatherproofer (WP1) Specifications

Disc Leveler and Hydraulic Flat Reel Combo Attachment

Adapts To:	2411-6-24	2411AFG-7-24	2411AFG-9-24	2431-11-24	2431-13-24
Approximate Weight	1,197 lbs. (543 kg)	4,022 lbs. (1824 kg)	4,827 lbs. (2,189 kg)	5,706 lbs. (2,588 kg)	6,500 lbs. (2,948 kg)
Disc Blades	18 in. (457 mm)	18 in. (457 mm)	18 in. (457 mm)	18 in. (457 mm)	18 in. (457 mm)
Number of Blades	2 per Shank	2 per Shank	2 per Shank	2 per Shank	2 per Shank
Chevron Reel	5-Blade, 13 in. (330 mm) Diameter	5-Blade, 13 in. (330 mm) Diameter	5-Blade, 13 in. (330 mm) Diameter	5-Blade, 13 in. (330 mm) Diameter	5-Blade, 13 in. (330 mm) Diameter
Reel Protection	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure
Independent Hydraulic Lift	Standard	Standard	Standard	Standard	Standard
Section Width	8 ft. (1.8 m) -- 8 ft. (1.8 m)	6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m)	6 ft. (1.8 m) -- 14 ft. (4.3 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 14 ft. (4.3 m) -- 8 ft. (1.8 m)