



2100 Series Coulter Chisel Specifications

Three Row Coil Tine Harrow

Adapts To:	2112-9	2112-11	2112-13	2112-15	2132-17	2132-19	2132-21	2132-23	2132-25
Approximate Weight	1,197 lbs. (543 kg)	1,310 lbs. (594 kg)	1,380 lbs. (626 kg)	1,450 lbs. (658 kg)	1,950 lbs. (885 kg)	2,020 lbs. (953 kg)	2,100 lbs. (953 kg)	2,190 lbs. (994 kg)	2,280 lbs. (1,034 kg)
Tines	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Coil Tine Protection	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs
Number of Sections	2	2	2	2	3	3	3	3	3
Independent Hydraulic Lift	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Weight Kit Required	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed	Yes, 4 Needed