



# 4630-36 FOLDING SEEDER



- Sure Stand Seeding...36 Feet in Every Pass
- 12' Seeder Sections Hug the Contour of the Field
- 69 Bushel Seed Box Capacity when Equipped with High Capacity Seeders
- Electric Shut Off Clutches Control Each 12' Seeder Individually
- Smooth Hydraulic Front Folding Feature Brings Transport Width to Less than 13' 6"
- Rugged Center Frame, Heavy-Duty Floating Wing Hinges, Proven Transport System
- Hydraulics and LED Safety Warning Lights are Standard Equipment





## 4630-36 Folding Seeder Shown with Standard Agricultural Seeders with Front and Rear Seed Boxes and Optional Folding Row Marker Kit



Folding Hydraulic Row Marker Kits are available as an option. Unique Brome Box Agitator Kits, Rear Rollers with Turfmaker Sprockets, and Front Roller Scraper Kits are also available as optional equipment to customize or enhance the performance of the 4630-36 Folding Seeder.

Each seeder is attached to the main frame via a three-point hitch, which allows the seeders to raise and lower in the field without changing the position of the main frame.

The center section is carried by 12.5L x 15 (GY-FI) Load F Tires with 8 Bolt Hubs and 2 7/8" Slip In Spindles.

4630 Seeder Console: Shaft sensors indicate which seeder sections are seeding. Each 12' seeder can be individually controlled. The Seed Shaft Monitor and Electric Clutches are standard equipment.

### 4630-36 SERIES SPECIFICATIONS

	SSBP-36	SSP-136
Description	(3) SSBP-12 Agricultural Seeders	(3) SSP-112 Agricultural Seeders
Approximate Weight (Empty)	18,440 lbs. (8,364 kg)	18,100 lbs. (8,210 kg)
Working Width	36 ft. (10.97 m)	36 ft. (10.97 m)
Transport Width	13 ft. 6 in. (4.1 m)	13 ft. 6 in. (4.1 m)
Transport Height	11 ft. (3.4 m)	11 ft. (3.4 m)
Overall Length	34 ft. (10.4 m)	34 ft. (10.4 m)
Hitch	Cast Single Lip Cat. IV	Cast Single Lip Cat. IV
Wheels - Center Section	8 Bolt Hubs with 2 7/8 in. (73.1 mm) Slip In Spindles	8 Bolt Hubs with 2 7/8 in. (73.1 mm) Slip In Spindles
Wheels - Wings	6 Bolt Hubs with 2 in. (50.8 mm) Spindles	6 Bolt Hubs with 2 in. (50.8 mm) Spindles
Tires - Center Section	(4) 12.5L x 15, (GY-FI) Load F	(4) 12.5L x 15, (GY-FI) Load F
Tires - Wings	(4) 11L x 15, 12 Ply	(4) 11L x 15, 12 Ply
Hydraulic Circuits Required	3 (+1 for Row Marker Kit)	3 (+1 for Row Marker Kit)
Seed Box	All Steel Construction	All Steel Construction
Seed Box Capacity	15.75 Bushels (555.0 l) Front / 15.75 (555.0 l) Bushels Rear	27 Bushels (951.5 l)
Seed Metering	Standard Micro-Meter Front / Blade Agitator Rear	Standard Micro-Meter
Seed Metering Drive	Independent Electric Seeder Clutches	Independent Electric Seeder Clutches
Pulverizer Rollers	Gray Cast Iron with Notched Profile	Gray Cast Iron with Notched Profile
Front Roller (Fixed)	14.5 in. (368.3 mm) Diameter	14.5 in. (368.3 mm) Diameter
Rear Roller (Independent Floating)	10.25 in. (260.4 mm) Diameter	10.25 in. (260.4 mm) Diameter
Cage Agitator for Rear Seed Box	Standard	NA
Brush Agitator for Rear Seed Box	Optional	NA
Seed Box Dividers	Standard, Front Box Only	Standard
Rear Roller Assembly with Turfmaker Sprockets	Optional	Optional
Folding Row Marker Kit	Optional	Optional
Wheel Track Removers - Wings	Standard	Standard
Coil Tine Track Remover Kit - Center Section	Standard	Standard
Front Roller Scraper Kit	Optional	Optional
Seed Shaft Monitor	Standard	Standard
Electronic Acre Meter Kit	Standard	Standard
LED Safety Warning Lights & SMV Emblem	Standard	Standard
Safety Chain Kit	Standard	Standard
Horsepower Requirements	Minimum of 200 HP (149.1 kW)	Minimum of 200 HP (149.1 kW)
Recommended Operating Speed	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions


Specifications subject to change without notice.



# 4630-36 FOLDING SEEDER



Operator's Manual Storage Canister




LED Safety Warning Lights

A Coil Tine Track Remover Kit is standard equipment for the center seeder section.

The wings are able to float up 14 degrees and down 14 degrees for superior contour following and precision seed placement.

The wings are equipped with 11L x 15, 12 Ply Tires with 6 Bolt Hubs and 2" Spindles.

The 4630-36 comes standard with three 12' three-point hitch seeders. Seeder choices are the standard series agricultural seeder with front and rear seed boxes, the mid-size agricultural seeder, or the high capacity agricultural seeder. The seeders are easily removed from the main frame and can be used as a standard 12' three-point hitch seeder.



Wheel Track Removers for the wing tires are standard equipment.

## SSP-2361

(3) SSP-2121 Agricultural Seeders

20,366 lbs. (9,238 kg)

36 ft. (10.97 m)

13 ft. 6 in. (4.1 m)

11 ft. (3.4 m)

34 ft. (10.4 m)

Cast Single Lip Cat. IV

8 Bolt Hubs with 2 7/8 in. (73.1 mm) Slip In Spindles

6 Bolt Hubs with 2 in. (50.8 mm) Spindles

(4) 12.5L x 15, (GY-FI) Load F

(4) 11L x 15, 12 Ply

3 (+1 for Row Marker Kit)

All Steel Construction

69 Bushels (2,431.5 l)

High Capacity Micro-Meter

Independent Electric Seeder Clutches

Gray Cast Iron with Notched Profile

14.5 in. (368.3 mm) Diameter

10.25 in. (260.4 mm) Diameter

NA

NA

Standard

Optional

Optional

Standard

Standard

Optional

Standard

Standard

Standard

Standard

Minimum of 200 HP (149.1 kW)

4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions



When folded, the 4630-36 is less than 13' 6" wide. There is also adequate ground clearance for safe road travel. Mechanical transport locks are provided for safety while traveling and when the machine is parked.





## 4630-36 Folding Seeder

Brillion Sure Stand Seeders have set the bar for exceptional grass and alfalfa seeding for well over fifty years. As production agriculture has grown, so has the demand for a larger capacity Sure Stand Seeder – and Brillion Farm Equipment has stepped up to meet the challenge. The Sure Stand seeding concept has stayed the same; however, thirty-six feet can now be seeded with each pass around the field!

Producers will have peace of mind that even though the seeding capacity has gone up, the 4630-36 will still afford the same industry leading performance the Brillion Sure Stand Seeder is famous for. The 4630-36 is a combination of the proven Landoll front folding grain drill hitch and the iconic Brillion twelve foot Sure Stand Seeder. This provides a state of the art machine with a quick transition from road transport of 13' 6" to a full seeding width in a matter of minutes, right from the comfort of the tractor cab. (Transport locks are required for safety purposes.)

One of the key features of the 4630-36 is the ability of the main frame to allow each of the three seeders to operate completely independently of each other. That equates to the ability to seed thirty-six feet wide with the convenience and field hugging features of a twelve foot machine. The individual, frame mounted three-point hitches raise and lower the seeders without changing the position of the main frame. This allows the operator to raise the seeders at the end of the field for effortless turning.

The design of the 4630-36 will allow the machine to be ordered with a choice of electric clutch controlled twelve foot seeders. The seed box capacity will vary with the model of seeders chosen. A variety of options and accessories are available to customize or enhance the performance of the 4630-36.



Also available from  
**Brillion Farm Equipment**



*Pulverizers*



*Pulvi-Mulchers*



*Food Plot Seeders*



*Till 'N Seed®*

**Brillion**  
Farm Equipment

220 N. Francis Street

P.O. Box 8

Brillion, WI 54110

Phone: 920.524.2220

Toll Free: 855.320.0373

Fax: 888.761.8568



[www.facebook.com/landollag](http://www.facebook.com/landollag)

4630-36\_0612\_Z\_0122

