

835/840 AG DETACHABLE GOOSENECK



- 60" or 44" Aluminum Ladder Ramps for Safe Easy Transition to Rear Deck



- 3 Stop Tail Turn with White Strobe LED Lights, Frame Prepped for Flip Third Axle - Standard



- Steel Frame Wood Decks, Hydraulic Flip Third Axle - Optional Equipment



- Easily Adjustable Ground Clearance in 2" Increments
- Transport at Any Height While Load Carrier is Seated



- RUST FREE Aluminum Pullouts to 13' Width (7,000 lb Capacity Each on 835) (10,000 lb Capacity Each on 840)
- Strong Aluminum Pullouts Save 1,000 lbs
- Pullouts Adjustable on 6" Increments
- "New" Aluminum Front Pullout Easily Adjusted by the Drivers



- Low Profile Front Approach
- Four Wheel or Tricycle Units Can be Easily Loaded, No Heavy Ramp
- Safe Loading Directly on Lower Deck
- Increased Driver Confidence While Loading



PROVEN SOLUTIONS FOR YOUR HAULING NEEDS!

1-800-428-5655 | www.landoll.com/trailers

STANDARD & OPTIONAL EQUIPMENT/FEATURES

835 / 840 Ag Detachable Gooseneck Trailer

S=Standard O=Optional

MODEL 835	35 TON	70,000 lbs
MODEL 840	40 TON	80,000 lbs
MAIN FRAME		
- Fabricated 100,000 PSI Four Beam Frame	S	S
- Capacity - 70,000 lb Distributed / 60,000 lb Concentrated in 12'	S	S
- Capacity - 80,000 lb Distributed in 16' / 60,000 lb Concentrated in 12'	S	
KINGPIN SETTING		
- 15" Pin Setting - 84" Swing Clearance 12' G/N	S	S
- 15" Pin Setting - 72" Swing Clearance 10'9"	O	O
CROSSMEMBERS		
- 5" x 3" High Tensile Strength Tubing on 18" Centers		S
- 6" x 3" High Tensile Strength Tubing on 18" Centers	S	
GOOSENECK, DECK AND ACCESSORIES		
- 12' Gooseneck	S	S
- 10'9" Gooseneck	O	O
- 102" Wide Removable Deck, Aluminum or Wood, Gooseneck and Trunnion (Rear Deck 2-Axle Trailers)	O	O
- 102" Width	S	S
- 120" Width (Select 835 Models)		O
- 18¼" Deck Height		S
- 19¼" Deck Height	S	
- 1½" Nominal, Apitong Full Width	S	S
- 27" Aluminum Telescoping Slide Out (Lower Deck)	S	S
- Flag and Banner Package (6 Flags & 2 Over Width Banners)	O	O
- Landoll Hoses and Components Certified to -40°F	S	S
TIE DOWNS / CHAIN GOTCHAS		
- Double Key Hole Chain Gotchas All (4) Frame Rails on 18" Centers	S	
- Double Key Hole Chain Gotchas Plate Located on 36" Centers		O
- (2) D-Rings Rear of Gooseneck	S	S
- Side Mounted D-Rings on 36" Centers		S
- (2) D-Rings at Base of Trunnion Flush Mounted on Top of Inner Beams	S	S
- (2) D-Rings Inner Web-Mounted Top of Trunnion	S	S
- (2) D-Rings Rear of Trunnion, Flush Mounted on Top of Inner Beams	S	S
- (2) D-Rings at Top of Trunnion Slope (Outer Web)	S	S
TOOL BOX		
- 24"H x 14"W x 22.5"D, Curb Side of Gooseneck, Galvanized	O	O
WINCHES AND ACCESSORIES		
- Worm Gear 12,000 lb with 85' of ½" Cable		O
- Worm Gear 20,000 lb with 85' of ⅝" Cable		O
- Planetary 20,000 lb with 85' of ⅝" Cable	O	O
- Planetary 30,000 lb with 85' of ⅝" Cable	O	O

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.

MODEL 835	35 TON	70,000 lbs
MODEL 840	40 TON	80,000 lbs
PULLOUTS		
- RUST FREE Aluminum Pullouts to 13' Width	S	S
- 7,000 lb Capacity Each, 835		S
- 10,000 lb Capacity Each, 840	S	
- (2) Planks for Bridging Aluminum Pullouts	O	O
AXLES		
- (2) 25,000 lb Dual Tire, Oil Bath Bearings	S	S
SUSPENSION		
- SAF-Holland / Neway Air Ride, Drum Brakes	S	S
- Centralized Grease System	S	S
- Air Raise / Lower Control and Suspension Dump Valve	S	S
- Digital Air Weigh Scale System	O	O
BRAKES / HUBS		
- Automatic Slack Adjusters / Drum Brakes		S
- 16.5 x 7 Full Air / Spring Brakes, ABS, 4S2M	S	S
- 22.5 x 8.25 Hub Pilot / Steel Outboard Hubs	S	S
- Air Disc Brakes with Dexter Suspension	O	O
TIRES		
- 255/70R 22.5 LRH Double Coin	S	S
- Spare Tire and Hub Pilot Type Rim (255/70R 22.5)	O	O
- PSI Tire Inflation System	O	O
WHEEL ACCESSORIES		
- Aluminum Wheels	O	O
- Hubdrometer	O	O
HYDRAULIC POWER SOURCE		
- Hydraulic Quick Couplers 2,500 PSI - 20 GPM at Controls, 50 GPM Max	S	S
- 11 HP Honda Engine Package Gooseneck Mounted with Cover	O	O
- 25 HP Kohler Engine Package Gooseneck Mounted with Cover	O	O
LIGHTS		
- Grote Rubber Grommet Mounted Annealed LED Lighting	S	S
- Grote "Xtreme" Wiring Harness (7-Year Warranty)	S	S
FINISH / COLOR		
- 400°F Bake / Steel Grit Shot Blast to Bright Metal	S	S
- TGIC Polyester Powder Coat	S	S
White, Black, Yellow, Blue, Red, Green, Metallic Gray, Sapphire Blue		
- Galvanized Finish for Gooseneck, Frame and Flip	O	O
ESTIMATED WEIGHT (BASE)		
- 835AG-53 / 840AG-53 Consult Factory		



SCAN FOR MORE



CALL 1-800-428-5655
REMEMBER: QUALITY IS ALWAYS A BARGAIN!

1900 North Street | Marysville, KS 66508 | Phone:785-562-5381 | Fax:888-293-6779