



# Pulverizer Specifications

P Series - No Transport Models - 5 ft. to 8 ft.

Product Attributes	P5	P6	P7	P8
<b>Approximate Weight</b>				
(PM) 16" Notched Gray Iron Wheels	715 lbs. (324 kg)	832 lbs. (377 kg)	949 lbs. (430 kg)	1,068 lbs. (484 kg)
(PD) 20" Notched Ductile Iron Wheels	651 lbs. (295 kg)	755 lbs. (342 kg)	859 lbs. (390 kg)	965 lbs. (438 kg)
(PC) 16" Crowfoot Gray Iron Wheels	684 lbs. (310 kg)	795 lbs. (361 kg)	906 lbs. (411 kg)	1,019 lbs. (462 kg)
<b>Working Width</b>	5 ft. 0 in. (1.5 m)	6 ft. 0 in. (1.8 m)	7 ft. 0 in. (2.1 m)	8 ft. 0 in. (2.4 m)
<b>Transport Width</b>	5 ft. 8 in. (1.7 m)	6 ft. 8 in. (2.0 m)	7 ft. 8 in. (2.3 m)	8 ft. 8 in. (2.6 m)
<b>Transport Height</b>	2 ft. 6 in. (0.8 m)	2 ft. 6 in. (0.8 m)	2 ft. 6 in. (0.8 m)	2 ft. 6 in. (0.8 m)
<b>Overall Length</b>	7 ft. 9 in. (2.4 m)	7 ft. 9 in. (2.4 m)	7 ft. 9 in. (2.4 m)	7 ft. 9 in. (2.4 m)
<b>Number of Pulverizer Wheels</b>				
(PM) 16" Notched Gray Iron Wheels	15	18	21	24
(PD) 20" Notched Ductile Iron Wheels	15	18	21	24
(PC) 16" Crowfoot Gray Iron Wheels	10	12	14	16
<b>Axle Size</b>	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)	4 in. (100 mm)
<b>Hitch</b>	Pull-Type/No Transport	Pull-Type/No Transport	Pull-Type/No Transport	Pull-Type/No Transport
<b>Scraper Kits</b>	Optional for PM & PD Series	Optional for PM & PD Series	Optional for PM & PD Series	Optional for PM & PD Series
<b>LED Safety Warning Lights &amp; SMV Emblem</b>	SMV Emblem Only	SMV Emblem Only	SMV Emblem Only	SMV Emblem Only
<b>Powder Coat Paint, Red</b>	Standard	Standard	Standard	Standard
<b>Horsepower Requirements</b>	35 HP (26.88 kW) and up	35 HP (26.88 kW) and up	45 HP (33.6 kW) and up	45 HP (33.6 kW) and up
<b>Recommended Operating Speed</b>	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)