



Pulverizer Specifications

SD Series - Double Gang Models

Product Attributes	SDP-6	SD-8	SDP-8	SD-10	SDP-10	SD-12	SDP-12
Approximate Weight	845 lbs. (380 kg)	1,886 lbs. (849 kg)	1,560 lbs. (702 kg)	2,188 lbs. (985 kg)	1,851 lbs. (833 kg)	2,386 lbs. (1,074 kg)	2,118 lbs. (953 kg)
Working Width	6 ft. 0 in. (1.8 m)	8 ft. 0 in. (2.4 m)	8 ft. 0 in. (2.4 m)	10 ft. 0 in. (3.0 m)	10 ft. 0 in. (3.0 m)	12 ft. 0 in. (3.6 m)	12 ft. 0 in. (3.6 m)
Transport Width	7 ft. 0 in. (2.1 m)	11 ft. 1 in. (3.4 m)	9 ft. 6 in. (2.9 m)	12 ft. 11 in. (3.9 m)	11 ft. 4 in. (3.5 m)	15 ft. 0 in. (4.6 m)	13 ft. 3 in. (4.0 m)
Transport Height	2 ft. 10 in. (1.0 m)	2 ft. 10 in. (1.0 m)	2 ft. 10 in. (1.0 m)	2 ft. 10 in. (1.0 m)	2 ft. 10 in. (1.0 m)	2 ft. 10 in. (1.0 m)	2 ft. 10 in. (1.0 m)
Overall Length	2 ft. 4 in. (.7 m)	13 ft. 2 in. (4.0 m)	5 ft. 6 in. (1.7 m)	13 ft. 2 in. (4.0 m)	5 ft. 6 in. (1.7 m)	13 ft. 2 in. (4.0 m)	5 ft. 6 in. (1.7 m)
Transport Tires	N/A	7.60 x 15-6 Ply Tires	N/A	7.60 x 15-6 Ply Tires	N/A	7.60 x 15-6 Ply Tires	N/A
Pulverizer Wheels, Front Gang	12 in. (300 mm) Gray Iron	16 in. (400 mm) Gray Iron	16 in. (400 mm) Gray Iron	16 in. (400 mm) Gray Iron	16 in. (400 mm) Gray Iron	16 in. (400 mm) Gray Iron	16 in. (400 mm) Gray Iron
Number of Wheels, Front Gang	31	40	40	50	50	61	61
Axle Size, Front Gang	8.625 in. (216 mm)	12.75 in. (319 mm)	12.75 in. (319 mm)	12.75 in. (319 mm)	12.75 in. (319 mm)	12.75 in. (319 mm)	12.75 in. (319 mm)
Pulverizer Wheels, Rear Gang	10 in. (250 mm) Gray Iron	12 in. (300 mm) Gray Iron	12 in. (300 mm) Gray Iron	12 in. (300 mm) Gray Iron	12 in. (300 mm) Gray Iron	12 in. (300 mm) Gray Iron	12 in. (300 mm) Gray Iron
Number of Wheels, Rear Gang	32	41	41	52	52	62	62
Axle Size, Rear Gang	1.75 in. (43.75 mm)	8.625 in. (216 mm)	8.625 in. (216 mm)	8.625 in. (216 mm)	8.625 in. (216 mm)	8.625 in. (216 mm)	8.625 in. (216 mm)
Hitch	Cat. I, II Free Link; Cat. I, II Quick Coupler	Pull-Type Hydraulic Transport	Cat. II Free Link; Cat. II, IIIN Quick Coupler	Pull-Type Hydraulic Transport	Cat. II Free Link; Cat. II, IIIN Quick Coupler	Pull-Type Hydraulic Transport	Cat. II Free Link; Cat. II, IIIN Quick Coupler
LED Safety Warning Lights & SMV Emblem	SMV Emblem Only	Standard	Standard	Standard	Standard	Standard	Standard
Safety Chain Kit	N/A	Standard	N/A	Standard	N/A	Standard	N/A
Powder Coat Paint, Red	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Horsepower Requirements	35 HP (26.88 kW) and up	55 HP (42.24 kW) and up	55 HP (42.24 kW) and up	65 HP (49.92 kW) and up	65 HP (49.92 kW) and up	80 HP (61.44 kW) and up	80 HP (61.44 kW) and up
Recommended Operating Speed	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)