



Sub Soiler Specifications

Product Attributes	SCP-1 / SCP-2	SCP-23 / SCPH-23	SCP-33 / SCPH-33
Approximate Weight	227 lbs. (104 kg) / 459 lbs. (208 kg)	688 lbs. (313 kg) / 708 lbs. (322 kg)	837 lbs. (381 kg) / 868 lbs. (395 kg)
Working Width	NA / 40 in. (1.01 m)	80 in. (2.03 m)	80 in. (2.03 m)
Transport Width	53 in. (1.35 m)	90 in. (2.29 m)	90 in. (2.29 m)
Transport Height	46 in. (1.17 m)	46 in. (1.17 m)	46 in. (1.17 m)
Number of Shanks	1 or 2	2	3
Shank Type	Rigid Parabolic with Shear Bolt	Rigid Parabolic with Shear Bolt	Rigid Parabolic with Shear Bolt
Shear Bolt Size	.625 in. x 3.75 in. (15.875 x 93.75 mm)	.625 in. x 3.75 in. (15.875 x 93.75 mm)	.625 in. x 3.75 in. (15.875 x 93.75 mm)
Shank Spacing	Up to 40 in. (100 mm)	Infinite on Tool Bar	Infinite on Tool Bar
Shank Working Depth	Maximum of 16 in. (400 mm)	Maximum of 16 in. (400 mm)	Maximum of 16 in. (400 mm)
Under Frame Clearance	29 in. (725 mm)	29 in. (725 mm) / 35 in. (875 mm)	29 in. (725 mm) / 35 in. (875 mm)
Points Available	2.5 in. (62.5 mm) Flat Steel Point	2.5 in. (62.5 mm) Flat Steel Point	2.5 in. (62.5 mm) Flat Steel Point
Wearstrips Available	Flat Wearstrip	Flat Wearstrip	Flat Wearstrip
Frame Structure	5 in. x 7 in. x .375 in. (125 x 175 x 9.52 mm)	4 in. x 6 in. x .25 in. (100 x 150 x 6.35 mm)	4 in. x 6 in. x .25 in. (100 x 150 x 6.35 mm)
Three-Point Hitch	Cat. I Free Link/ Cat. II Free Link	Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch
Powder Coat Paint, Red	Standard	Standard	Standard
Horsepower Requirements	20 to 40 HP (14.9 to 29.8 kW) per Shank [Horsepower not to exceed 40 HP per Shank]	20 to 40 HP (14.9 to 29.8 kW) per Shank [Horsepower not to exceed 40 HP per Shank]	20 to 40 HP (14.9 to 29.8 kW) per Shank [Horsepower not to exceed 40 HP per Shank]
Recommended Operating Speed	4 to 6 MPH (6.43 to 9.65 km/h)	4 to 6 MPH (6.43 to 9.65 km/h)	4 to 6 MPH (6.43 to 9.65 km/h)