



2400 Series Weatherproofer (WP1) Specifications

Chopper and Chevron Reel Combo Attachment

Adapts To:	2411-6-24	2411AFG-7-24	2411AFG-9-24	2431-11-24	2431-13-24
Approximate Weight	3,456 lbs. (1,568 kg)	4,617 lbs. (2,094 kg)	4,901 lbs. (2,223 kg)	5,296 lbs. (2,402 kg)	5,960 lbs. (2,703 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Chopper Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Chopper Reel Protection	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex
Chevron Reel Diameter	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Chevron Reel Rod Diameter	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)
Chevron Reel Protection	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure
Independent Hydraulic Lift	Standard	Standard	Standard	Standard	Standard
Hydraulic Lift and Parrallel Lift Arms	NA	Optional	Optional	NA	NA
Section Width	7 ft. 7 in. (2.3 m) -- 8 ft. 9 in. (2.7 m)	4 ft. 7 in. (1.4 m) -- 9 ft. 6 in. (2.9 m) -- 4 ft. 7 in. (1.4 m)	6 ft. 10 in. (2.1 m) -- 8 ft. 9 in. (2.7 m) -- 6 ft. 10 in. (2.1 m)	6 ft. 10 in. (2.1 m) -- 13 ft. (4.0 m) -- 6 ft. 10 in. (2.1 m)	8 ft. 9 in. (2.7 m) -- 13 ft. (4.0 m) -- 8 ft. 9 in. (2.7 m)