



Agricultural Seeder Specifications

4610-16 Models

Product Attributes	SS16	SSP16	SSB16	SSBP16
Approximate Weight	7,450 lbs. (3,379 kg)	6,125 lbs. (2,778 kg)	8,030 lbs. (3,642 kg)	6,610 lbs. (2,998 kg)
Working Width	16 ft. 0 in. (4.9 m)	16 ft. 0 in. (4.9 m)	16 ft. 0 in. (4.9 m)	16 ft. 0 in. (4.9 m)
Transport Width	18 ft. (5.5 m)	18 ft. (5.5 m)	18 ft. (5.5 m)	18 ft. (5.5 m)
Transport Height	7 ft. 6 in. (2.3 m)	Tractor Dependent	7 ft. 0 in. (2.1 m)	Tractor Dependent
Transport Length	17 ft. 7 in. (5.4 m)	8 ft. 3 in. (2.5 m)	17 ft. 7 in. (5.4 m)	7 ft. 5 in. (2.3 m)
Road Clearance	16 in. (406 mm)	Tractor Dependent	16 in. (406 mm)	Tractor Dependent
Working Overall Height	5 ft. 9 in. (1.8 m)	5 ft. 9 in. (1.8 m)	5 ft. 7 in. (1.7 m)	5 ft. 7 in. (1.7 m)
Working Overall Length	18 ft. 8 in. (5.7 m)	8 ft. 3 in. (2.5 m)	18 ft. 8 in. (5.7 m)	7 ft. 5 in. (2.3 m)
Seed Boxes	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover
Seed Box Capacity (Micro-Meter)	20 bu.	20 bu.	20 bu.	20 bu.
Seed Box Capacity (Agitator)	N/A	N/A	10 bu.	10 bu.
Seed Metering System	Micro-Meter	Micro-Meter	Micro-Meter / Blade Agitator	Micro-Meter / Blade Agitator
Seed Metering System Drive	Ground Driven	Ground Driven	Ground Driven	Ground Driven
Seed Meter/Agitator Opening Spacing	8 in. (203 mm)	8 in. (203 mm)	8 in. (203 mm) / 4 in. (102 mm)	8 in. (203 mm) / 4 in. (102 mm)
Seed Delivery	Broadcast with Wind Deflector	Broadcast with Wind Deflector	Broadcast with Wind Deflector	Broadcast with Wind Deflector
Pulverizer Roller - Front	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron
Pulverizer Roller - Rear	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron
Pulverizer Axle Bearings	1.75 in. (45 mm) Flange Bearing Sealed	1.75 in. (45 mm) Flange Bearing Sealed	1.75 in. (45 mm) Flange Bearing Sealed	1.75 in. (45 mm) Flange Bearing Sealed
Pulverizer Axle Size - Front	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)
Pulverizer Axle Size - Rear	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)
Rear Roller Pneumatic Down Pressure	Standard	Standard	Standard	Standard
Hitch Type	Pull-Type with Hydraulic Transport	Three-Point Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch
Hitch Category	Cat. II, III Hitch	Cat. II, III Free Link; Cat. II, IIIN, III Quick Coupler Hitch	Cat. II, III Hitch	Cat. II, III Free Link; Cat. II, IIIN, III Quick Coupler Hitch
Tire Size	(4) 11L x 15, 12 Ply Implement Rib	N/A	(4) 11L x 15, 12 Ply Implement Rib	N/A
Blade Agitator	N/A	N/A	Standard	Standard
Cage Agitator	N/A	N/A	Optional	Optional
5-Strip Brush Agitator	N/A	N/A	Optional	Optional
8-Row Brush Agitator	N/A	N/A	Optional	Optional
S-Tine Wheel Track Remover	Optional	Optional	Optional	Optional
Hydraulic S-Tine Track Remover	Optional	Optional	Optional	Optional
Coil Tine Wheel Track Remover	Optional	Optional	Optional	Optional
Electric Clutch	Standard	Standard	Standard	Standard
Electronic Acre Meter	Optional	Optional	Optional	Optional
Brillion Elite Mini Monitor System	Optional	Optional	Optional	Optional
Seed Box Scale System	Optional	Optional	Optional	Optional
Safety Warning Lights & SMV Emblem	Standard	Standard	Standard	Standard
Safety Chain Kit	Standard	N/A	Standard	N/A
Powder Coat Paint, Red	Standard	Standard	Standard	Standard
Horsepower Requirements	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.
Required Three-Point Hitch Lift Capacity	N/A	8,000 lbs. (3,629 kg) Minimum	N/A	9,000 lbs. (4,082 kg) Minimum
Recommended Operating Speed	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions

Specifications subject to change with or without notice.