

POWER DITCHER





Model D5P18A, D10P18A, and D10PH18A

- 540 RPM on D5P18A, and 1,000 RPM on D10P18A and D10PH18A
- Cutter head adjustable from 18" to 20", with 4 heat treated replaceable blades 740 RPM rotor speed
- Adjustable cutting depth by regulating depth control skid and 3-point hitch
- Chain case, 6" x 10" with bolt on top and bottom caps, uses double 80 chain and case hardened 16 tooth top sprocket and 22 tooth bottom sprocket for DP10 models. Sprockets are reversed on D5P18A
- · Cat. II or III, 3-point or quick hitch
- (2) Shear bolts, 3/8" grade 8
- (2) Parking stands
- Recommended PTO HP: 50-100 with 540 PTO for D5P18A
- Recommended PTO HP: 80-150 with 1,000 PTO for D10P18A and D10PH18A
- · Sapphire Blue Powder Coat Paint Standard







MODEL SPECIFICATIONS

Model Number	PTO RPM	Coupler Size	Estimated Weight
D5P18A	540	13/8"	525
D10P18A	1,000	13/8"	525
D10PH18A	1,000	1¾"	530



1900 North Street • Marysville, KS 66508 • (785) 738-6613 • www.landoll.com





