



# 8500 Series Finishroll Specifications

## Three Row Spike and Reel

Adapts To:	8530-19	8530-22	8530-25
Approximate Weight	2,519 lbs. (1,143 kg)	2,641 lbs. (1,197 kg)	2,926 lbs. (1,327 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	3 in. (76.2 mm)	3 in. (76.2 mm)	3 in. (76.2 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional
Section Sizes	6 ft. (1.8 m) -- 9 ft. (2.7 m) -- 6 ft. (1.8 m)	7.5 ft. (2.3 m) -- 9 ft. (2.7 m) -- 7.5 ft. (2.3 m)	8.25 ft. (2.5 m) -- 9.75 ft. (3.0 m) -- 8.25 ft. (2.5 m)

Adapts To:	8530-27	8530-30	8530-33
Approximate Weight	3,498 lbs. (1,587 kg)	3,904 lbs. (1,771 kg)	4,026 lbs. (1,826 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	3 in. (76.2 mm)	3 in. (76.2 mm)	3 in. (76.2 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional	Optional
Section Sizes	8.25 ft. (2.5 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 8.25 ft. (2.5 m)	9.75 ft. (3.0 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 9.75 ft. (3.0 m)	10.5 ft. (3.2 m) -- 6.75 ft. (2.1 m) -- 6.75 ft. (2.1 m) -- 10.5 ft. (3.2 m)

Adapts To:	8530-35	8550-38
Approximate Weight	4,821 lbs. (2,187 kg)	5,006 lbs. (2,271 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	3 in. (76.2 mm)	3 in. (76.2 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional
Section Sizes	11.25 ft. (3.4 m) -- 6.75 ft. (2.1 m) -- 7.5 ft. (2.3 m) -- 11.75 ft. (3.6 m)	6 ft. (1.8 m) -- 7.5 ft. (2.3 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 7.5 ft. (2.3 m) -- 6 ft. (1.8 m)

Adapts To:	8550-43	8550-48
Approximate Weight	5,215 lbs. (2,365 kg)	5,516 lbs. (2,502 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	3 in. (76.2 mm)	3 in. (76.2 mm)
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)
Spike Angle Adjustment	2 Position Adjustment	2 Position Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	Round Bar Chevron OR Flat Blade	Round Bar Chevron OR Flat Blade
Reel Hydraulic Lift	Optional	Optional
Section Sizes	7.5 ft. (2.3 m) -- 8.25 ft. (2.5 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 8.25 ft. (2.5 m) -- 7.5 ft. (2.3 m)	9.75 ft. (3.0 m) -- 9 ft. (2.7 m) -- 6.75 ft. (2.1 m) -- 6 ft. (1.8 m) -- 9 ft. (2.7 m) -- 9.75 ft. (3.0 m)