



9600 Series Field Cultivator Specifications

Flexible Five Row Spike Harrow

9430/9630 Three-Section Folding Models

| Adapts To: | 9630-20 | 9630-24 | 9630-28 | 9630-30NC |
|------------------------|--|---|--|---|
| Approximate Weight | 2,042 lbs. (926 kg) | 2,160 lbs. (980 kg) | 2,675 lbs. (1,213 kg) | 2,789 lbs. (1,265 kg) |
| Teeth | 0.75 in. x 14 in. (19.1 x 356 mm) | 0.75 in. x 14 in. (19.1 x 356 mm) | 0.75 in. x 14 in. (19.1 x 356 mm) | 0.75 in. x 14 in. (19.1 x 356 mm) |
| Teeth Spacing | 1.8 in. (45.7 mm) | 1.8 in. (45.7 mm) | 1.8 in. (45.7 mm) | 1.8 in. (45.7 mm) |
| Distance Between Bars | 14 in. (356 mm) | 14 in. (356 mm) | 14 in. (356 mm) | 14 in. (356 mm) |
| Spike Angle Adjustment | 2 Position Adjustment | 2 Position Adjustment | 2 Position Adjustment | 2 Position Adjustment |
| Section Sizes | 6 ft. (1.8 m) -- 10.5 ft. (3.2 m) -- 6 ft. (1.8 m) | 7.5 ft. (2.3 m) -- 11.25 ft. (3.4 m) -- 7.5 ft. (2.3 m) | 9.75 ft. (3.0 m) -- 10.5 ft. (3.2 m) -- 9.75 ft. (3.0 m) | 10.5 ft. (3.2 m) -- 11.25 ft. (3.4 m) -- 10.5 ft. (3.2 m) |

| Adapts To: | 9630-30/9630-30FH | 9630-32/9630-32FH | 9630-34/9630-34FH |
|------------------------|---|---|---|
| Approximate Weight | 2,921 lbs. (1,324 kg) | 2,980 lbs. (1,352 kg) | 3,100 lbs. (1,406 kg) |
| Teeth | 0.75 in. x 14 in. (19.1 x 356 mm) | 0.75 in. x 14 in. (19.1 x 356 mm) | 0.75 in. x 14 in. (19.1 x 356 mm) |
| Teeth Spacing | 1.8 in. (45.7 mm) | 1.8 in. (45.7 mm) | 1.8 in. (45.7 mm) |
| Distance Between Bars | 14 in. (356 mm) | 14 in. (356 mm) | 14 in. (356 mm) |
| Spike Angle Adjustment | 2 Position Adjustment | 2 Position Adjustment | 2 Position Adjustment |
| Section Sizes | 9.75 ft. (3.0 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 9.75 ft. (3.0 m) | 10.5 ft. (3.2 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 10.5 ft. (3.2 m) | 12 ft. (3.7 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 12 ft. (3.7 m) |

9450/9650 Five-Section Folding Models

| Adapts To: | 9650-38/9650-38FH | 9650-42/9650-42FH |
|------------------------|---|---|
| Approximate Weight | 3,742 lbs. (1,697 kg) | 3,857 lbs. (1,750 kg) |
| Teeth | 0.75 in. x 14 in. (19.1 x 356 mm) | 0.75 in. x 14 in. (19.1 x 356 mm) |
| Teeth Spacing | 1.8 in. (45.7 mm) | 1.8 in. (45.7 mm) |
| Distance Between Bars | 14 in. (356 mm) | 14 in. (356 mm) |
| Spike Angle Adjustment | 2 Position Adjustment | 2 Position Adjustment |
| Section Sizes | 6 ft. (1.8 m) -- 8.25 ft. (2.5 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 8.25 ft. (2.5 m) -- 6 ft. (1.8 m) | 7.5 ft. (2.3 m) -- 8.25 ft. (2.5 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 8.25 ft. (2.5 m) -- 7.5 ft. (2.3 m) |

| Adapts To: | 9650-46/9650-46FH | 9650-50/9650-50FH |
|------------------------|---|---|
| Approximate Weight | 4,034 lbs. (1,830 kg) | 4,151 lbs. (1,883 kg) |
| Teeth | 0.75 in. x 14 in. (19.1 x 356 mm) | 0.75 in. x 14 in. (19.1 x 356 mm) |
| Teeth Spacing | 1.8 in. (45.7 mm) | 1.8 in. (45.7 mm) |
| Distance Between Bars | 14 in. (356 mm) | 14 in. (356 mm) |
| Spike Angle Adjustment | 2 Position Adjustment | 2 Position Adjustment |
| Section Sizes | 8.25 ft. (2.5 m) -- 9.75 ft. (3.0 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 9.75 ft. (3.0 m) -- 8.25 ft. (2.5 m) | 9.75 ft. (3.0 m) -- 9.75 ft. (3.0 m) -- 5.75 ft. (1.8 m) -- 6.5 ft. (2.0 m) -- 9.75 ft. (3.0 m) -- 9.75 ft. (3.0 m) |