



1900 Series Filloll - Pivot Track Closer

Product Attributes	1911-9	1911-11
Approximate Weight	5,370 lbs. (2,436 kg)	5,780 lbs. (2,622 kg)
Working Width	9 ft. 0 in. (2.7 m)	11 ft. 4 in. (3.5 m)
Transport Width	9 ft. 9 in. (3.0 m)	12 ft. 4 in. (3.9 m)
Number of Blades	16	20
Blade Size	24 in. (610 mm) x 0.25 in. (6.35 mm) Smooth Rollable	24 in. (610 mm) x 0.25 in. (6.35 mm) Smooth Rollable
Blade Spacing	7 in. (178 mm)	7 in. (178 mm)
Blade Scrapers	5.5 in. (140 mm) Adjustable	5.5 in. (140 mm) Adjustable
Blade Scraper Mount	Heavy-Duty 0.5 in. (12.7 mm) x 1.75 in. (44.5 mm) Spring Steel Arm	Heavy-Duty 0.5 in. (12.7 mm) x 1.75 in. (44.5 mm) Spring Steel Arm
Gang Spools	6 in. (152 mm) Diameter - Solid Cast	6 in. (152 mm) Diameter - Solid Cast
Gang Angle	Adjustable from 10 to 18 Degrees	Adjustable from 10 to 18 Degrees
Gang Shaft	1.75 in. (44.5 mm) Round	1.75 in. (44.5 mm) Round
Gang Bearings	C-Cushion Trunnion Mount with Greaseable Triple Lip Seals	C-Cushion Trunnion Mount with Greaseable Triple Lip Seals
Center Cut Out Blades	(2) 22 in. (559 mm) x 0.25 in. (6.35 mm) Notched	(2) 22 in. (559 mm) x 0.25 in. (6.35 mm) Notched
Frame Construction	Laser Cut/Matchcut Components, Robotically Welded	Laser Cut/Matchcut Components, Robotically Welded
Frame Size	6 in. x 4 in. x 0.25 in. (153 mm x 102 mm x 6.35 mm) Frame Tubes	6 in. x 4 in. x 0.25 in. (153 mm x 102 mm x 6.35 mm) Frame Tubes
Transport Lift Axles	4.5 in. (114 mm) with Maintenance Free Bearings	4.5 in. (114 mm) with Maintenance Free Bearings
Transport Axle Type	Single Wheels	Single Wheels
Tire Size	(2) 320/70R x 15 Radial Tires	(2) 320/70R x 15 Radial Tires
Wheel Hubs	8-Bolt	8-Bolt
Spindles	2.25 in. (57.2 mm) Slip-In Spindles	2.25 in. (57.2 mm) Slip-In Spindles
Hitch Leveling	Hydraulic Front to Rear Leveling	Hydraulic Front to Rear Leveling
Hitch Category	Cat. III Cast Single Lip Ball Hitch	Cat. III Cast Single Lip Ball Hitch
Leveling Attachment	Hydraulic Double 12 in. (305 mm) Flat Blade Reels	Hydraulic Double 12 in. (305 mm) Flat Blade Reels
Safety Chain Kit, LED Warning Lights & SMV Emblem	Standard	Standard
Paint, Blue Sapphire	Standard	Standard
Spare Tire and Wheel Assembly	Optional	Optional
Cat. IV Cast Single Lip Ball Hitch	Optional	Optional
Double Lip Hitch Clevis	Optional	Optional
Guide Centering Cones	Optional	Optional
Center Packer Wheels	Optional	Optional
Single 14 in. (356 mm) Chevron Reel	Optional in Lieu of Double Flat Blade Reels	Optional in Lieu of Double Flat Blade Reels
Horsepower Requirements	15 HP (11 kW) per Foot	15 HP (11 kW) per Foot