



1900 FILLOLL - PIVOT TRACK CLOSER



FILLLOLL SPECIFICATIONS

STANDARD EQUIPMENT

Frame:

- 6" x 4" x 1/4" frame tubes
- Hydraulic front to rear leveling

Transport:

- (2) 320/70R x 15, radial tires with 8-bolt wheels and 2 1/4" slip in spindles

Blades:

- Individually mounted 24" x 1/4" smooth blades on 7" spacing
- Hydraulic adjustable blade angle 10-18°, max angle will drag soil like a box scraper

Leveling Attachment:

- Double 12" diameter flat blade reels
- Optional 14" diameter single chevron reel

Other:

- Single lip Cat. III with ball hitch
- Safety chain, light kit, and SMV emblem
- Blue powder coat paint
- Gang and adjustment wrenches

AVAILABLE OPTIONS

- Double lip hitch with 1 1/16" hole
- Spare tire/wheel assy. 320/70R x 15
- Hydraulic lift chevron reel in lieu of double flat blade reels

3 YEAR WARRANTY



MODEL SPECIFICATIONS

Model Number	Number of Blades	Blade Spacing	Transport Width	Estimated Weight
1911-9	16	7"	9' 4"	5,285 lb



1900 North Street • Marysville, KS 66508 • (785) 738-6613 • www.landoll.com

Landoll continuously improves products. We reserve the right to make any changes in illustrations, specifications, equipment, and prices without prior notice and without changes on previous models.

