



Agricultural Seeder Specifications

Mid-Size Series (8 ft. to 12 ft.)

Product Attributes	SS-108	SSP-108	SS-110	SSP-110	SS-112	SSP-112
Approximate Weight	2,420 lbs. (1,098 kg)	2,031 lbs. (921 kg)	2,819 lbs. (1,279 kg)	2,429 lbs. (1,102 kg)	3,217 lbs. (1,459 kg)	2,958 lbs. (1,342 kg)
Working Width	8 ft. 0 in. (2.4 m)	8 ft. 0 in. (2.4 m)	10 ft. 0 in. (3.0 m)	10 ft. 0 in. (3.0 m)	12 ft. 0 in. (3.6 m)	12 ft. 0 in. (3.6 m)
Transport Width	11 ft. 6 in. (3.5 m)	9 ft. 6 in. (2.9 m)	13 ft. 4 in. (4.1 m)	11 ft. 3 in. (3.4 m)	15 ft. 5 in. (4.7 m)	13 ft. 6 in. (4.1 m)
Transport Height	4 ft. 11 in. (1.5 m)	Tractor Dependent	4 ft. 11 in. (1.5 m)	Tractor Dependent	4 ft. 11 in. (1.5 m)	Tractor Dependent
Road Clearance	10 in. (254 mm)	Tractor Dependent	10 in. (254 mm)	Tractor Dependent	10 in. (254 mm)	Tractor Dependent
Overall Height	3 ft. 10 in. (1.2 m)	4 ft. 3 in. (1.3 m)	3 ft. 10 in. (1.2 m)	4 ft. 3 in. (1.3 m)	3 ft. 10 in. (1.2 m)	4 ft. 3 in. (1.3 m)
Overall Length	10 ft. 1 in. (3.1 m)	4 ft. 0 in. (1.2 m)	10 ft. 1 in. (3.1 m)	4 ft. 0 in. (1.2 m)	10 ft. 1 in. (3.1 m)	4 ft. 0 in. (1.2 m)
Seed Box	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover
Seed Box Capacity - Meter Box	6 bu.	6 bu.	7.5 bu.	7.5 bu.	9.0 bu.	9.0 bu.
Seed Meters	Micro-Meter	Micro-Meter	Micro-Meter	Micro-Meter	Micro-Meter	Micro-Meter
Seed Meter Drive	Ground Driven	Ground Driven	Ground Driven	Ground Driven	Ground Driven	Ground Driven
Seed Meter Spacing	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)
Seed Delivery	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray
Pulverizer Roller - Front	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron
Pulverizer Roller - Rear	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron
Pulverizer Axle Bearings	Greaseable	Greaseable	Greaseable	Greaseable	Greaseable	Greaseable
Pulverizer Axle Size - Front	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)
Pulverizer Axle Size - Rear	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)
Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch
Hydraulic Equipment	Cylinders with Hoses to Hitch Point	N/A	Cylinders with Hoses to Hitch Point	N/A	Cylinders with Hoses to Hitch Point	N/A
Tire Size	9.5L x 15-8 Ply Implement Rib	N/A	9.5L x 15-8 Ply Implement Rib	N/A	9.5L x 15-8 Ply Implement Rib	N/A
S-Tine Wheel Track Remover	Optional	Optional	Optional	Optional	Optional	Optional
Coil Tine Track Remover	Optional	Optional	Optional	Optional	Optional	Optional
Front Roller Scraper Kit	Optional	Optional	Optional	Optional	Optional	Optional
Electronic Acre Meter Kit	Optional	Optional	Optional	Optional	Optional	Optional
Factory Installed Electric Clutch	Optional	Optional	Optional	Optional	Optional	Optional
Brillion Elite Mini Monitor	Optional	Optional	Optional	Optional	Optional	Optional
Speed Up Kit (Doubles Output)	Optional	Optional	Optional	Optional	Optional	Optional
Safety Warning Lights & SMV Emblem	Standard	Standard	Standard	Standard	Standard	Standard
Safety Chain Kit	Standard	N/A	Standard	N/A	Standard	N/A
Powder Coat Paint, Red	Standard	Standard	Standard	Standard	Standard	Standard
Horsepower Requirements	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.
Recommended Operating Speed	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)