



Agricultural Seeder Specifications

Small Ag Series (4 ft. to 6 ft.)

Product Attributes	SSBP-4	SSBP-5	SSBP-6	SSBS-6
Approximate Weight	888 lbs. (403 kg)	1,061 lbs. (481 kg)	1,205 lbs. (547 kg)	1,401 lbs. (636 kg)
Working Width	4 ft. 0 in. (1.2 m)	5 ft. 0 in. (1.25 m)	6 ft. 0 in. (1.8 m)	6 ft. 0 in. (1.8 m)
Transport Width	5 ft. 0 in. (1.25 m)	6 ft. 0 in. (1.8 m)	7 ft. 0 in. (2.1 m)	7 ft. 0 in. (2.1 m)
Transport Height	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor
Overall Height	4 ft. 5 in. (1.4 m)			
Overall Length	2 ft. 6 in. (0.8 m)			
Seed Box	All Steel Construction with Cover			
Seed Box Capacity - Front Seed Box	1.75 bu.	2.187 bu.	2.625 bu.	2.625 bu.
Seed Box Capacity - Rear Seed Box	1.75 bu.	2.187 bu.	2.625 bu.	2.625 bu.
Seed Meter - Front Seed Box	Micro-Meter	Micro-Meter	Micro-Meter	Micro-Meter
Seed Meter - Rear Seed Box	Blade Agitator or 5-Strip Brush Agitator			
Seed Meter Drive	Ground Driven	Ground Driven	Ground Driven	Ground Driven
Seed Meter Spacing - Front Seed Box	8 in. (203 mm)	8.5 in. (216 mm)	6 in. (152 mm)	6 in. (152 mm)
Seed Opening Spacing - Rear Seed Box	4 in. (102 mm)	4.25 in. (108 mm)	4 in. (102 mm)	4 in. (102 mm)
Seed Delivery	Broadcast with Wind Deflector Tray			
Pulverizer Roller - Front	11.5 in. (292 mm) Cast Iron			
Pulverizer Roller - Rear	9.5 in. (241 mm) Cast Iron			
Pulverizer Axle Bearings	Greaseable	Greaseable	Greaseable	Greaseable
Pulverizer Axle Size - Front	8.625 in. (219 mm)			
Pulverizer Axle Size - Rear	1.75 in. (44.5 mm)			
Coil Tine Track Remover	Standard	Standard	Standard	Standard
Hitch Type	Three-Point Hitch	Three-Point Hitch	Three-Point Hitch	Skid Steer Quick Attach Plate; Three-Point Hitch
Hitch Category	Cat. I, II Free Link; Cat. I Quick Coupler Hitch	Cat. I, II Free Link; Cat. I Quick Coupler Hitch	Cat. I, II Free Link; Cat. I Quick Coupler Hitch	Cat. I, II Free Link; Cat. I Quick Coupler Hitch
Cat. II Quick Coupler Hitch Adaptor Kit	Optional	Optional	Optional	Optional
Spike Roller - Front (6 ft.)	N/A	N/A	Optional	Optional
Notched Rear Roller w/Sprockets	Optional	Optional	Optional	Optional
Notched Rear Heavy Roller w/Sprockets (6 ft.)	N/A	N/A	Optional	Optional
Blade Agitator Kit for Rear Seed Box (Field Install)	Optional	Optional	Optional	Optional
5-Strip Brush Agitator Kit for Rear Seed Box (Field Install)	Optional	Optional	Optional	Optional
8-Row Brush Agitator Kit for Rear Seed Box (Field Install)	Optional	Optional	Optional	Optional
Electronic Acre Meter Kit	Optional	Optional	Optional	Optional
Lift Sling Kit	Optional	Optional	Optional	Optional
Speed Up Kit (Doubles Output)	Optional	Optional	Optional	Optional
SMV Emblem	Standard	Standard	Standard	Standard
Powder Coat Paint, Red	Standard	Standard	Standard	Standard
Horsepower Requirements	35 HP (26.88 kW) and up			
Recommended Operating Speed	3 to 5 MPH (5 to 8.3 km/h)	3 to 5 MPH (5 to 8.3 km/h)	3 to 5 MPH (5 to 8.3 km/h)	3 to 5 MPH (5 to 8.3 km/h)