



Agricultural Seeder Specifications

Standard Series (8 ft. to 12 ft.)

Product Attributes	SSB-8	SSBP-8	SSB-10	SSBP-10	SSB-12	SSBP-12
Approximate Weight	2,612 lbs. (1,185 kg)	2,315 lbs. (1,050 kg)	2,971 lbs. (1,348 kg)	2,505 lbs. (1,136 kg)	3,383 lbs. (1,535 kg)	3,041 lbs. (1,379 kg)
Working Width	8 ft. 0 in. (2.4 m)	8 ft. 0 in. (2.4 m)	10 ft. 0 in. (3.0 m)	10 ft. 0 in. (3.0 m)	12 ft. 0 in. (3.6 m)	12 ft. 0 in. (3.6 m)
Transport Width	11 ft. 6 in. (3.5 m)	9 ft. 7 in. (2.9 m)	13 ft. 5 in. (4.1 m)	11 ft. 5 in. (3.5 m)	15 ft. 6 in. (4.7 m)	13 ft. 6 in. (4.1 m)
Transport Height	4 ft. 10 in. (1.5 m)	Tractor Dependent	4 ft. 10 in. (1.5 m)	Tractor Dependent	4 ft. 10 in. (1.5 m)	Tractor Dependent
Road Clearance	10 in. (254 mm)	Tractor Dependent	10 in. (254 mm)	Tractor Dependent	10 in. (254 mm)	Tractor Dependent
Overall Height	3 ft. 9 in. (1.1 m)	4 ft. 3 in. (1.3 m)	3 ft. 9 in. (1.1 m)	4 ft. 3 in. (1.3 m)	3 ft. 9 in. (1.1 m)	4 ft. 3 in. (1.3 m)
Overall Length	10 ft. 1 in. (3.1 m)	4 ft. 1 in. (1.2 m)	10 ft. 1 in. (3.1 m)	4 ft. 1 in. (1.2 m)	10 ft. 1 in. (3.1 m)	4 ft. 1 in. (1.2 m)
Seed Box	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover
Seed Box Capacity - Front Seed Box	3.5 bu.	3.5 bu.	4.375 bu.	4.375 bu.	5.25 bu.	5.25 bu.
Seed Box Capacity - Rear Seed Box	3.5 bu.	3.5 bu.	4.375 bu.	4.375 bu.	5.25 bu.	5.25 bu.
Seed Meter - Front Seed Box	Micro-Meter	Micro-Meter	Micro-Meter	Micro-Meter	Micro-Meter	Micro-Meter
Seed Meter - Rear Seed Box	Blade Agitator or 5-Strip Brush Agitator	Blade Agitator or 5-Strip Brush Agitator	Blade Agitator or 5-Strip Brush Agitator	Blade Agitator or 5-Strip Brush Agitator	Blade Agitator or 5-Strip Brush Agitator	Blade Agitator or 5-Strip Brush Agitator
Seed Meter Drive	Ground Driven	Ground Driven	Ground Driven	Ground Driven	Ground Driven	Ground Driven
Seed Meter Spacing - Front Seed Box	8 in. (203 mm)	8 in. (203 mm)	8.5 in. (216 mm)	8.5 in. (216 mm)	6 in. (152 mm)	6 in. (152 mm)
Seed Opening Spacing - Rear Seed Box	4 in. (102 mm)	4 in. (102 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)	4 in. (102 mm)	4 in. (102 mm)
Seed Delivery	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray
Pulverizer Roller - Front	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron	15.75 in. (400 mm) Cast Iron
Pulverizer Roller - Rear	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron	11.5 in. (292 mm) Cast Iron
Pulverizer Axle Bearings	Greaseable	Greaseable	Greaseable	Greaseable	Greaseable	Greaseable
Pulverizer Axle Size - Front	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)
Pulverizer Axle Size - Rear	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)
Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch
Hydraulic Equipment	Cylinders with Hoses to Hitch Point	N/A	Cylinders with Hoses to Hitch Point	N/A	Cylinders with Hoses to Hitch Point	N/A
Tire Size	9.5L x 15-8 Ply Implement Rib	N/A	9.5L x 15-8 Ply Implement Rib	N/A	9.5L x 15-8 Ply Implement Rib	N/A
Balde Agitator Kit for Rear Seed Box (Field Install)	Optional	Optional	Optional	Optional	Optional	Optional
5-Strip Brush Agitator Kit for Rear Seed Box (Field Install)	Optional	Optional	Optional	Optional	Optional	Optional
Cage Agitator Kit for Rear Seed Box (Field Install)	Optional	Optional	Optional	Optional	Optional	Optional
S-Tine Wheel Track Remover	Optional	Optional	Optional	Optional	Optional	Optional
Coil Tine Track Remover	Optional	Optional	Optional	Optional	Optional	Optional
Front Roller Scraper Kit	Optional	Optional	Optional	Optional	Optional	Optional
Seed Box Divider Kit	Standard on Front Box; Optional on Rear Box	Standard on Front Box; Optional on Rear Box	Standard on Front Box; Optional on Rear Box	Standard on Front Box; Optional on Rear Box	Standard on Front Box; Optional on Rear Box	Standard on Front Box; Optional on Rear Box
Electronic Acre Meter Kit	Optional	Optional	Optional	Optional	Optional	Optional
Brilliant Elite Mini Monitor	Optional	Optional	Optional	Optional	Optional	Optional
Speed Up Kit (Doubles Output)	Optional	Optional	Optional	Optional	Optional	Optional
Factory Installed Electric Clutch	Optional	Optional	Optional	Optional	Optional	Optional
Safety Warning Lights & SMV Emblem	Standard	Standard	Standard	Standard	Standard	Standard
Safety Chain Kit	Standard	N/A	Standard	N/A	Standard	N/A
Powder Coat Paint, Red	Standard	Standard	Standard	Standard	Standard	Standard
Horsepower Requirements	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.
Recommended Operating Speed	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)