



Pulvi-Mulcher Specifications

3620 Series

Product Attributes	WLB-3620-21
Approximate Weight	21,353 lbs. (9,686 kg)
Working Width	21 ft. 0 in. (6.4 m)
Transport Width	12 ft. 3 in. (3.7 m)
Transport Height	13 ft. 4 in. (4.1 m)
Overall Length (Transport)	31 ft. 3 in. (9.5 m)
Road Clearance	13 in. (330 mm)
Type of Pulverizer Wheel - Front	24 in. (610 mm) Notched Ductile Iron
Number of Pulverizer Wheels - Front	64
Type of Pulverizer Wheel - Rear	24 in. (610 mm) Notched Ductile Iron
Number of Pulverizer Wheels - Rear	65
Rear Roller Scrapers	Standard
Roller Axle Size	8 in. (203 mm)
Bearing Type	61 mm Heavy-Duty
Type of Shanks	Heavy-Duty Two-Piece Edge Bent S-Tine Shank 1.75 in. x 0.625 in. (44.5 x 15.9 mm)
Number of Shanks	42
Points	2 in. (51 mm) Reversible
Nominal Shank Spacing	6 in. (152 mm)
Maximum Shank Depth of Operation	5 in. (127 mm)
Under Frame Clearance	25 in. (635 mm)
Two-Row Coil Tine Harrow	Standard (In Front of Rear Roller)
Hitch	Pull-Type with Hydraulic Lift
Hitch Category	Cat. II, III or IV (Cat. V Optional)
Floating Hitch	Standard, Hitch Floats 15 Degrees Up and 25 Degrees Down
Wing Float	Wings Float 5 Degrees Down
Tire Size	(4) 12.5L x 15 FI
Hydraulic Circuits Required	3 (+1 for Rear Hitch)
Rear Hitch	Optional
Front Roller Scraper Kit	Optional
V-Leveler Kit	Optional
Hydraulic Down Pressure System	Standard
Independent Hydraulic Tooth Depth Control	Standard
LED Warning Lights & SMV Emblem	Standard
Safety Chain Kit	Standard
Powder Coat Paint	Standard
Horsepower Requirements	10 to 14 HP (7.5 to 10.4 kW) per ft.
Recommended Operating Speed	6 to 8 MPH (10 to 13 km/h)