



2700 Series VertiSTRIP - Strip Till

Product Attributes	2710-8x30	2730-12x30	2730-16x22	2730-16x30
Approximate Weight	TBD	11,700 lbs. (5,307 kg)	14,300 lbs. (6,486 kg)	15,500 lbs. (7,031 kg)
Working Width	8 Rows on 30 in. (762 mm) Spacing	12 Rows on 30 in. (762 mm) Spacing	16 Rows on 22 in. (559 mm) Spacing	16 Rows on 30 in. (762 mm) Spacing
Transport Width	TBD	17 ft. 3 in. (5.3 m)	17 ft. 3 in. (5.3 m)	19 ft. 9 in. (6.0 m)
Unit Height (Less Three-Point Hitch Lift Height)	TBD	9 ft. 2 in. (2.8 m)	9 ft. 2 in. (2.8 m)	10 ft. 8 in. (3.3 m)
Frame Construction	7 in. x 7 in. x 0.375 in. (178 x 178 x 9.5 mm) Double Bar Frame	7 in. x 7 in. x 0.375 in. (178 x 178 x 9.5 mm) Double Bar Frame	7 in. x 7 in. x 0.5 in. (178 x 178 x 12.7 mm) Center Frame	7 in. x 7 in. x 0.5 in. (178 x 178 x 12.7 mm) Center Frame
			7 in. x 7 in. x 0.375 in. (178 x 178 x 9.5 mm) Wing Frame	7 in. x 7 in. x 0.375 in. (178 x 178 x 9.5 mm) Wing Frame
Hitch Type	Mounted Three-Point Hitch	Mounted Three-Point Hitch	Mounted Three-Point Hitch	Mounted Three-Point Hitch
Hitch Category	Cat. III, IV	Cat. III, IV	Cat. IV	Cat. IV
Trailblazer™ Row Cleaners	Floating with Adjustable Down Pressure	Floating with Adjustable Down Pressure	Floating with Adjustable Down Pressure	Floating with Adjustable Down Pressure
Trailblazer Design	Staggered 13 in. (330 mm) Fingers with 10 in. (254 mm) Float Wheel	Staggered 13 in. (330 mm) Fingers with 10 in. (254 mm) Float Wheel	Staggered 13 in. (330 mm) Fingers with 10 in. (254 mm) Float Wheel	Staggered 13 in. (330 mm) Fingers with 10 in. (254 mm) Float Wheel
Trailblazer Bearings	Sealed Bearings	Sealed Bearings	Sealed Bearings	Sealed Bearings
Lead Coulter Blade Size	18 in. (457 mm) Directional Coulter Blade	18 in. (457 mm) Directional Coulter Blade	18 in. (457 mm) Directional Coulter Blade	18 in. (457 mm) Directional Coulter Blade
Lead Coulter Blade Adjustment	2 in., 3 in. or 4 in. (50.8, 76.2 or 102 mm) Relative to Gauge Wheels	2 in., 3 in. or 4 in. (50.8, 76.2 or 102 mm) Relative to Gauge Wheels	2 in., 3 in. or 4 in. (50.8, 76.2 or 102 mm) Relative to Gauge Wheels	2 in., 3 in. or 4 in. (50.8, 76.2 or 102 mm) Relative to Gauge Wheels
Shank Type	Rigid Shear Bolt	Rigid Shear Bolt	Rigid Shear Bolt	Rigid Shear Bolt
Shank Size	1 in. x 3.375 in. (25.4 x 85.7 mm)	1 in. x 3.375 in. (25.4 x 85.7 mm)	1 in. x 3.375 in. (25.4 x 85.7 mm)	1 in. x 3.375 in. (25.4 x 85.7 mm)
Shank Depth Adjustment	4 in. to 8 in. (102 to 203 mm) in 0.5 in. (12.7 mm) Increments	4 in. to 8 in. (102 to 203 mm) in 0.5 in. (12.7 mm) Increments	4 in. to 8 in. (102 to 203 mm) in 0.5 in. (12.7 mm) Increments	4 in. to 8 in. (102 to 203 mm) in 0.5 in. (12.7 mm) Increments
Ground Engaging Option	Mole Knife with Dual Fertilizer Tubes	Mole Knife with Dual Fertilizer Tubes	Mole Knife with Dual Fertilizer Tubes	Mole Knife with Dual Fertilizer Tubes
FlexBerm™ Conditioning System	Standard with Shank/Knife Option	Standard with Shank/Knife Option	Standard with Shank/Knife Option	Standard with Shank/Knife Option
FlexBerm Conditioning System Blade Size	(2) 18 in. (457 mm) Coulter Blades	(2) 18 in. (457 mm) Coulter Blades	(2) 18 in. (457 mm) Coulter Blades	(2) 18 in. (457 mm) Coulter Blades
FlexBerm Conditioning System Adjustment	2 to 18 Degrees	2 to 18 Degrees	2 to 18 Degrees	2 to 18 Degrees
Coulter Strip-Tillage	Optional in lieu of Knife and FlexBerm Conditioning System	Optional in lieu of Knife and FlexBerm Conditioning System	Optional in lieu of Knife and FlexBerm Conditioning System	Optional in lieu of Knife and FlexBerm Conditioning System
Coulter Strip-Tillage Blade Size	(2) 18 in. (457 mm) Direction Blades	(2) 18 in. (457 mm) Direction Blades	(2) 18 in. (457 mm) Direction Blades	(2) 18 in. (457 mm) Direction Blades
Coulter Strip-Tillage Blade Spacing	3.5 in. (88.9 mm)	3.5 in. (88.9 mm)	3.5 in. (88.9 mm)	3.5 in. (88.9 mm)
Coulter Strip Tillage Working Depth Range	1 in. to 5 in. (25.4 to 127 mm)	1 in. to 5 in. (25.4 to 127 mm)	1 in. to 5 in. (25.4 to 127 mm)	1 in. to 5 in. (25.4 to 127 mm)
Finishing Reel Diameter	16 in. (406 mm) Flat Blade Reel	16 in. (406 mm) Flat Blade Reel	16 in. (406 mm) Flat Blade Reel	16 in. (406 mm) Flat Blade Reel
Finishing Reel Width	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)
Finishing Reel Adjustment	Pneumatic Down Pressure Adjustable from Tractor	Pneumatic Down Pressure Adjustable from Tractor	Pneumatic Down Pressure Adjustable from Tractor	Pneumatic Down Pressure Adjustable from Tractor
Loup 2700 Elite Monitor	Standard	Standard	Standard	Standard
On-Board 12-Volt Air Compressor	Standard	Standard	Standard	Standard
LED Warning Lights & SMV Emblem	Standard	Standard	Standard	Standard
Front and Rear Jack Stands	Standard	Standard	Standard	Standard
Paint, Blue Sapphire	Standard	Standard	Standard	Standard
Factory Assembly	Standard	Standard	Standard	Standard
Rear Hitch to Pull Tanks	Optional	Optional	Optional	Optional
Horsepower Requirements	25 HP (19 kW) per Row	25 HP (19 kW) per Row	25 HP (19 kW) per Row	25 HP (19 kW) per Row